

**Zoom in Picture** 

### **■** Features

- 2x RS422 / RS485
- 32-bit universal PCI
- Optical Isolation 2KV
- Supports 64 Byte FIFO Driver
- Embedded 16KV ESD protection
- Support Automatic Data Direction Control (ADDC)
- Built-in termination resistors
- Compact board size (half-siz

# CP-132U-I PCI

Quick Link: | Features | Overview | Applications | Specification | Hardware | Interface | Performance | Configuration | Power and Environment | Ordering Information |

#### Overview

The CP-132 Universal PCI series is designed the new slot standard for expansion Boards and works with both 3.3V and 5.0V server slots.CP 132U offers two independent RS422 / 485, and each port can control up to 32 devices in a multidrop environment.

## Applications

- Industrial control
  Multiport data acquisition
- Embedded industrial machine Factory automation
  - Remote serial device control

## Specification

#### ■ Hardware

I/O controller 2x 16C550C or compatible

Connector type Male DB9

>Back to top

## Interface

Bus interface 32-bit Universal PCI, for 3.3V and 5.0V expansion Slots

Serial interface RS422 / 485

No. of ports 2

Signals RS422 TxD+/-, RxD+/-, RTS+/-, CTS+/-, GND

RS485 Data+/-, GND

RS485 data control Auto (Automatic Data Direction Control) or by RTS

Built-in termination RS422 120 Ohm

resistor RS485 120 Ohm, jumper enable / disable

>Back to top

#### Performance

**Speed** 50 - 230.4Kbps

Max. no. of ports	8 (4 boards)	
		>Back to top
■ Configuration		
Parity	None, even, odd, space, mark	
Data bits	5, 6, 7, 8	
Stop bits	1, 1.5, 2	
IRQ	Assigned by BIOS	
I/O address	Assigned by BIOS	

## ■ Power and Environment

Power requirement	580mA max.(+5V)	
Operation temp.	0°C - 55°C	
Dimension	120mm x 100mm	
Isolation Protection	16KV ESD protection 2 KV Optical Isolation	
Operating Systems supported	XP, Windows 2000, Windows NT, Windows 95/98/ME, Linux	
	>Back to top	

## Ordering Information

Art.No	747	
Product Name	CP-132U-I PCI	
Packing list	CP-132U-I PCI Software CD, English documentation 2 Port DB9 male connection cable Standard Bracket	
		>Back to top

■ Full size product image



>Back to top