



[Zoom in Picture](#)

■ Features

- 2x RS422 / RS485
- Support Automatic Data Direction Control (ADDC)
- Built-in termination resistors
- Compact board size (half-size), suitable for any PC cabinet
- On-chip hardware flow control, no data loss
- Support optical isolation, max.

CP-132I PCI

Quick Link: | [Features](#) | [Overview](#) | [Applications](#) | [Specification](#) | [Hardware](#) | [Interface](#) | [Performance](#) | [Configuration](#) | [Power and Environment](#) | [Ordering Information](#) |

■ Overview

The CP-132 series is designed for RS422 / 485 industrial communication. It supports 2 independent RS422 or RS485 ports, and each port can control up to 32 devices in a multidrop environment. Applications can easily manage the data transmitting and r

■ Applications

- Industrial control
- Embedded industrial machine
- SCADA
- Multiport data acquisition
- Factory automation
- Remote serial device control

■ Specification

■ Hardware

I/O controller	2x 16C550C or compatible, each with 16 bytes Tx/Rx FIFO
Connector type	Male DB9

[>Back to top](#)

■ Interface

Bus interface	PCI version 2.1 (32bit)
Serial interface	RS422 / 485
No. of ports	2
Signals	RS422 TxD+/-, RxD+/-, RTS+/-, CTS+/-, GND RS485 Data+/-, GND
RS485 data control	Auto (Automatic Data Direction Control) or by RTS
Built-in termination resistor	RS422 120 Ohm RS485 120 Ohm, jumper enable / disable

[>Back to top](#)

■ Performance

Speed	50 - 921.6Kbps
--------------	----------------

Max. no. of ports	8 (4 boards)
--------------------------	--------------

[>Back to top](#)

■ Configuration

Parity	None, even, odd, space, mark
---------------	------------------------------

Data bits	5, 6, 7, 8
------------------	------------

Stop bits	1, 1.5, 2
------------------	-----------

IRQ	Assigned by BIOS
------------	------------------

I/O address	Assigned by BIOS
--------------------	------------------

[>Back to top](#)

■ Power and Environment

Power requirement	700mA max.(+5V)
--------------------------	-----------------

Operation temp.	0°C - 55°C
------------------------	------------

Dimension	120mm x 110mm
------------------	---------------

Isolation Protection	2KV
-----------------------------	-----

Operating Systems supported	XP, Windows 2000, Windows NT, Windows 95/98/ME, DOS
------------------------------------	---

[>Back to top](#)

■ Ordering Information

Art.No	735
---------------	-----

Product Name	CP-132I PCI
---------------------	-------------

Packing list	CP-132I PCI with optical isolation (2KV) CD, English documentation PComm Lite serial comm developing tool
---------------------	---

[>Back to top](#)

■ Full size product image



[>Back to top](#)