



[Zoom in Picture](#)

### ■ Features

- 2x RS422 / RS485
- Support Automatic Data Direction Control (ADDC)
- Built-in termination resistors
- Compact board size (half-size), suitable for any PC cabinet
- On-chip hardware flow control, no data loss
- available as CP 132UL Universal

## CP-132 PCI

Quick Link: | [Features](#) | [Overview](#) | [Applications](#) | [Specification](#) | [Hardware](#) | [Interface](#) | [Performance](#) | [Configuration](#) | [Power and Environment](#) | [Ordering Information](#) |

### ■ Overview

The CP-132 series is designed for RS422 / 485 industrial communication. It supports 2 independent RS422 or RS485 ports, and each port can control up to 32 devices in a multidrop environment. Applications can easily manage the data transmitting and r

### ■ Applications

- Industrial control
- Embedded industrial machine
- SCADA
- Multiport data acquisition
- Factory automation
- Remote serial device control

### ■ Specification

#### ■ Hardware

<b>I/O controller</b>	2x 16C550C or compatible, each with 16 bytes Tx/Rx FIFO
<b>Connector type</b>	Male DB9

[>Back to top](#)

### ■ Interface

<b>Bus interface</b>	PCI version 2.1 (32bit)
<b>Serial interface</b>	RS422 / 485
<b>No. of ports</b>	2
<b>Signals</b>	RS422 TxD+/-, RxD+/-, RTS+/-, CTS+/-, GND RS485 Data+/-, GND
<b>RS485 data control</b>	Auto (Automatic Data Direction Control) or by RTS
<b>Built-in termination resistor</b>	RS422 120 Ohm RS485 120 Ohm, jumper enable / disable

[>Back to top](#)

### ■ Performance

**Speed**

50 - 921.6Kbps  
CP132UL, CP132UI PCI up to 230.4Kbps

**Max. no. of ports**

8 (4 boards)

[>Back to top](#)

**■ Configuration****Parity**

None, even, odd, space, mark

**Data bits**

5, 6, 7, 8

**Stop bits**

1, 1.5, 2

**IRQ**

Assigned by BIOS

**I/O address**

Assigned by BIOS

[>Back to top](#)

**■ Power and Environment****Power requirement**

430mA max.(+5V)

**Operation temp.**

0°C - 55°C

**Dimension**

120mm x 80mm

**Operating Systems supported**

XP, Windows 2000, Windows NT, Windows 95/98/ME, DOS

[>Back to top](#)

**■ Ordering Information****Art.No**

733

**Product Name**

CP-132 PCI

**Packing list**

CP-132 PCI card  
CD, English documentationPCComm Lite serial comm developing tool

**Also available**

Art.No 748  
CP132UL PCI Low Profile  
Universal PCI 3.3V/5.0V  
Dimension 120x65mm, DB25 to 4xDB9 cable, standard and Low Profile bracket included

Art.No. 747  
CP132UI  
Universal PCI 3.3V/5.0V  
2KV optical isolation, 16KV embedded

[>Back to top](#)

**■ Full size product image**



[>Back to top](#)