


[Zoom in Picture](#)

## ■ Features

- 4x RS232
- 4x 16C550 UARTs (16 Byte FIFO, max. 921 kbps)
- possible I/O-addresses 0h..FFFh
- no jumper, configured by software
- Software compatibel with DOS, Win3.x/95/98/ME/NT 4.0, Win2000, Linux, OS/2, Netware

# C104H

Quick Link: | [Features](#) |

|                                    |   |
|------------------------------------|---|
| Ports                              | 4 x RS232   |
| UART                               | 4x 16C550 (16 Byte FIFO)  |
| Address                            | 0h .. FFF8h   |
| Interrupts                         | IRQ2 .. IRQ15, supports <b>Interruptsharing</b>   |
| Speed                              | max. 921 kbps   |
| Bus interface                      | ISA   |
| Connectors                         | 1x DB37 female  |
| Size                               | L15.7cm x H8.3cm  |
| Temperature                        | 0°C - 55°C  |
| <b>Operating Systems supported</b> | compatible to DOS, Win3.x/95/98/ME/NT/2000, OS/2, Unix, Linux and Netware                                   |
| Driver                             | DOS, Win3.x/95/NT, Linux  |
| Ordering Information               | Moxa C104H Pro, cable (DB37 to 4 x DB25 male, cablelength 30 cm), disk (DOS, Windows), German documentation |

[>Back to top](#)

■ [Full size product image](#)



[>Back to top](#)