

Model Information



■ Features

- Intel Celeron M, 1GHz without fan
- 1GB DDR2, max. 2GB
- 8 x LAN / 2 x USB 2.0 / 1 x RS232
- Compact Flash Adapter, HDD Space (SATA)
- MiniPCI Socket
- Dimensions 250mm x 180mm x 44mm

[Contact Online...](#)

EmRunner 5622

Quick Link: | [Features](#) | [More Pictures](#) | [Overview](#) | [System](#) | [Storage](#) | [Chassis](#) | [Power Requirements](#) | [Environment](#) | [Ordering Information](#) |

■ More Pictures



Klick on the thumbnails for the large picture ...

[>Back to top](#)

■ Overview

The really small and robust embedded system! Low Power Consumption, Professional construction inside!

■ System

CPU

Intel Celeron M Processor
(512KB cache, 1GHz)

Chipset:

Intel 910GML E + ICH6

Memory

1GB DDR2 (2GB max.)
2x 240-pin DIMM

I/O Interface Front

- 2x USB2.0 ports
- DB9 serial port RS232
- HDD access/power/LAN status LEDs

I/O Interface Rear

- 4x GbE LAN ports (Intel RTL8111C Chipset)
- 4x LAN ports (Intel RTL8100C Chipset) 2x USB 2.0 ports
- DB15 VGA port
- 12-24V DC power input
- ATX power on/off switch and reset button

[>Back to top](#)

■ Storage

HDD/SSD

1x 2.5" SATA HDD drive bay

Flash

1x internal CF socket

[>Back to top](#)

■ Chassis

| | |
|---------------------------------|---|
| Construction | Aluminium chassis with fanless design |
| Expansion slot | 1x miniPCIe |
| Dimensions | 250 x 180 x 44 mm |
| >Back to top | |
| ■ Power Requirements | |
| DC | 12V - 24V DC on-board power support |
| AC | 19V, 60W external power adapter |
| >Back to top | |
| ■ Environment | |
| Operating Temp. | 0°C - 50°C |
| Storage Temp. | -20°C – 80°C |
| >Back to top | |
| ■ Ordering Information | |
| Part number | 3175 EmRunner 5622 |
| Packing list | EmRunner 5622 Embedded System (incl. CPU 1GHz, 1GB DDR2 RAM) Power supply Driver CD, English documentation |
| >Back to top | |

