

Model Information



■ Features

- AMD Geode LX 800, 500MHz without fan, inkl. 512MB DDR SoDIMM, VGA on board
- 1 x LAN / 4 x USB 2.0
- 2x RS232
- Compact Flash Adapter
- Power Supply AC-DC 24W or DC 12-24V terminal block
- Dimensions 123.0mm x 120.0mm x 44mm
- HDD Space
- Keyboard/Mouse connector

[Contact Online...](#)

EmRunner 5201

Quick Link: | [Features](#) | [More Pictures](#) | [Overview](#) | [System](#) | [Storage](#) | [Chassis](#) | [Power Requirements](#) | [Power Consumption](#) | [Environment](#) | [Ordering Information](#) | [optional](#) |

■ More Pictures



Klick on the thumbnails for the large picture ...

[>Back to top](#)

■ Overview

The really small and robust embedded system! Fan less, Low Power Consumption, Professional construction inside!

■ System

CPU	AMD Geode LX-800 Processor (128KB cache, 500 MHz)
Chipset:	AMD Geode CS5536
Memory	512MB DDR (1GB max.) 1x 200-Pin SoDIMM
I / O Interface Front	• 4x USB 2.0 ports • HDD access/power/LAN status LEDs
I / O Interface Rear	• 1x LAN ports (Realtek RTL8100C Chipset) • 1x DB15 VGA port • 2x DB9 serial port RS232 • 1x PS/2 for keyboard/mouse • 1x earphone-out • 1x mic-in • 12-24V DC power input • AT power on/off switch

[>Back to top](#)

■ Storage

HDD / SSD	1x 2.5" PATA HDD drive bay
------------------	----------------------------

Flash	1x internal CF socket
>Back to top	
■ Chassis	
Construction	Aluminium chassis with fanless design
Dimensions	123x 120x 44mm
>Back to top	
■ Power Requirements	
DC	12V - 24V DC on-board power support
AC	19V, 60W external power adapter
>Back to top	
■ Power Consumption	
with power supply	ca. 15W
average system alone	ca. 6.9W
>Back to top	
■ Environment	
Operating Temp.	0°C - 50°C
Storage Temp.	-20°C – 80°C
>Back to top	
■ Ordering Information	
Part number	215 EmRunner 5201
Packing list	EmRunner 5201 Embedded System CD, English documentation power supply, with power cord 2 x L-type universal fixers with 4 screws 1 x 44-pin flat cable and 4 screws for fixing and connecting hdd 1 x 2-pin apertable terminal block 1 x PS-2 Y cable for keyboard/mouse
>Back to top	
■ optional	
Memory	DDR up to 1GB
Mass Storage device	2.5 HDD PATA Compact Flash Card
>Back to top	

EmRunner 5201

[>Back](#)

