

Model Information



■ Features

- AMD Geode LX 800, 500MHz without fan, inkl. 512MB DDR SoDIMM, VGA on board
- 1 x LAN / 4 x USB 2.0
- 2x RS232
- Compact Flash Adapter
- Power Supply AC-DC 24W or DC 12-24V terminal block
- Dimensions 123.0mm x 120.0mm x 44mm
- HDD Space
- Keyboard/Mouse connector

[Contact Online...](#)

EmRunner 5205

Quick Link: | [Features](#) | [More Pictures](#) | [Overview](#) | [System](#) | [Storage](#) | [Chassis](#) | [Power Requirements](#) | [Power Consumption](#) | [Environment](#) | [Ordering Information](#) | [optional](#) |

■ More Pictures



Klick on the thumbnails for the large picture ...

[>Back to top](#)

■ Overview

The really small and robust embedded system! Fan less, Low Power Consumption, Professional construction inside!

■ System

CPU

AMD Geode LX-800 Processor
(128KB cache, 500 MHz)

Chipset:

AMD Geode CS5536

Memory

512MB DDR (1GB max.)
1x 200-Pin SoDIMM

I / O Interface Left

- 12-24V DC power input
- 1x LAN ports (Realtek RTL8100C Chipset)
- 2x USB 2.0 ports
- 1x DB15 VGA port
- 1x DB9 serial port RS232
- 1x PS/2 for keyboard/mouse
- HDD access/power/LAN status LEDs
- 1x earphone-out
- 1x mic-in
- AT power on/off switch

I / O Interface Rear
[>Back to top](#)

■ Storage

HDD/SSD

1x 2.5" PATA HDD drive bay

Flash	1x internal CF socket	>Back to top
■ Chassis		
Construction	Aluminium chassis with fanless design	
Expansion slot	2x mini card + SIM	
Dimensions	123 x 120 x 44 mm	>Back to top
■ Power Requirements		
DC	12V - 24V DC on-board power support	
AC	19V, 60W external power adapter	>Back to top
■ Power Consumption		
with power supply	ca. 15W	
average system alone	ca. 6.9W	>Back to top
■ Environment		
Operating Temp.	0°C - 50°C	
Storage Temp.	-20°C – 80°C	>Back to top
■ Ordering Information		
Part number	226 EmRunner 5205	
Packing list	EmRunner 5205 Embedded System CD, English documentation power supply, with power cord 2 x L-type universal fixers with 4 screws 1 x 44-pin flat cable and 4 screws for fixing and connecting hdd 1 x 2-pin apertable terminal block 1 x PS-2 Y cable for keyboard/mouse	>Back to top
■ optional		
WLAN	IEEE 802.11b WLAN Module with Antenna	
Memory	DDR up to 1GB	
Mass Storage device	2.5 HDD PATA Compact Flash Card	>Back to top

