



[Zoom in Picture](#)

■ Features

- Supports Intel Core 2 Duo, Core Duo, Celeron M
- Intel 945GME Chipset
- up to 4GB DDR2 Memory
- 2x GigaLAN / 4 x USB 2.0 / Mic-in / Audio
- 4x RS232
- Compact Flash Adapter / HDD Space S-ATA
- 1 x PCIe 16, 2 x PCI Expansion Slot
- Dimensions 200 x 126 x 238mm

VS-Trojan X

Quick Link: | [Features](#) | [Overview](#) | [Chassis](#) | [Hardware](#) | [Memory](#) | [Video](#) | [Integrated Devices](#) | [Connectivity](#) | [Power supply](#) | [Power consumption](#) | [Environment](#) | [Software](#) | [Ordering Information](#) |

■ Overview

Ultra High Performance System, Professional construction inside!
best solution for industrial area

■ Chassis

Construction	Heavy duty steel
Mounting configuration	Desktop, Wallmount
Filter	no
Cooling system	1 x ball bearing Chassis fan
LED indicator	Power on/off in front , HDD/CF access , 2 x LAN access
Expansion slot	1 x PCIe 16, 2 x 32-bit PCI Expansion Slot
Dimensions	200 x 126 x 238mm
Power switch	in front

[>Back to top](#)

■ Hardware

Processor	Intel Core 2 Duo, Core Duo, Celeron M
CPU socket	Socket 479 uFCPGA
Front side BUS	533 / 677 MHz
BIOS	Phoenix Award Flash BIOS
Chipset	Intel 945GME

[>Back to top](#)

■ Memory

Memory type	DDR2 _{up to 4GB}
Memory socket	two 240-pin DDR2 DIMM socket

[>Back to top](#)

■ Video

VGA controller	embedded in Chipset Intel 945GME
-----------------------	----------------------------------

BUS	4x AGP internal in chipset
Video RAM	up to 128MB dynamic video memory
Interface	VGA
Resolutions	up to 2048 x 1536/32bit
>Back to top	
■ Integrated Devices	
IDE	optional 2.5 HDD, SATA
FDD	no
CD-ROM/DVD	no
Compact Flash	complete built in Optional 512MB, 1GB, 2GB, 4GB, 8GB Compact Flash Card
PCMCIA	no
DiskonChip	no
Specials	Mic-in, 1 x Speaker-out
Watch dog Timer	Programmable watchdog timer, 1-63 sec.
Real Time clock	standard
Keyboard/Mouse	PS/2 connector for Keyboard and Mouse
>Back to top	
■ Connectivity	
LAN	2 x RJ45, 10/100/1000BaseTx with Intel chipset 82573L supports PXE Boot from LAN
USB	4 x USB 2.0 supports boot function from USB
IEEE 1394	no
VGA	1 x 15-pin connector
Com Ports total	4 x DSUB 9 male
Com Port Modi	4 x RS232
LPT	no
Audio	Line-in (Mic-in) Line-out ear-jet connectors
TV-out	no
S-Video	no
>Back to top	
■ Power supply	
external Power Adapter	155W
Power input	AC 100-240V, 50-60Hz
Power output	+5V, 8A, +12V , 8A
>Back to top	
■ Power consumption	
average system only	NN
with power supply	NN
>Back to top	
■ Environment	
Operating Temp.	0°-50°C
Storage Temp.	-20°-+80°C
>Back to top	

■ Software

Windows 2K, XP, Embedded XP, Vista

Linux Kernel 2.4 / 2.6

[>Back to top](#)

■ Ordering Information

Art.No 268

Product Name VS Trojan X

Packing list VS-Trojan X
CD, English documentation
Power Adapter AC 230V

[>Back to top](#)

■ Full size product image



[>Back to top](#)