

Model Information



■ Features

- Intel Atom J1900, 2.0GHz Quadcore, 2GB DDR3
- VGA /HDMI
- 4 x GLAN / 3 x USB 2.0 / 2 x RS232/485
- 2 x MiniPCIe Socket + 1 x SIM
- HDD Space S-ATA
- Power supply DC 12V
- Dimensions 210.0mm x 125.0mm x 55mm

[Contact Online...](#)

FlexRunner 2516

[Quick Link:](#) | [Features](#) | [More Pictures](#) | [Overview](#) | [System](#) | [Storage](#) | [Chassis](#) | [Power Requirements](#) | [Environment](#) | [Ordering Information](#) |

■ More Pictures



Click on the thumbnails for the large picture ...

[>Back to top](#)

■ Overview

The really small, robust and powerful embedded system! Fan less, ultra High Performance, Low Power Consumption, Professional construction inside!

best solution for Thin Client, Internet Appliances, VoIP, Networking and Multimedia

■ System

CPU Intel Atom Bay Trail J1900 Processor
2.0GHz Quadcore

Memory 2GB DDR3 (4GB max.)
1x SoDIMM

I/O Interface Rear

- 4x GbE LAN ports (Intel I210AT Chipset)
- 3x USB 2.0 ports
- 1x DB15 VGA port
- 1x HDMI port
- 2x DB9 serial port RS232/485
- 1x SIM-card slot
- 12V DC power input
- power on/off button

[>Back to top](#)

■ Storage

HDD/SSD 1x 2.5" SATA HDD drive bay
1x mSATA

[>Back to top](#)

■ Chassis

Construction Aluminium chassis with fanless design

Expansion slot	2x miniPCIe (1x mSATA)	
Dimensions	210x 125x 55mm	>Back to top
■ Power Requirements		
DC	12V DC on-board power support	
AC	60W external power adapter	>Back to top
■ Environment		
Operating Temp.	0°C - 45°C for HDD "-20°C - 70°C for mSATA	
Storage Temp.	-20°C – 80°C	>Back to top
■ Ordering Information		
Part number	127 FlexRunner 2516	
Packing list	FlexRunner 2516 Embedded System (incl. CPU 2.0GHz, 2GB DDR3 RAM) Power supply Driver CD, English documentation	>Back to top

FlexRunner 2516

[>Back](#)

