

Model Information



■ Features

- Can control 8x RS232 devices located virtually anywhere (via Ethernet or Internet)
- LAN interface 10BaseT/100BaseTx Ethernet
- Driver automatically finds NetCom devices in the network
- Configuration over Driver Panels, serial Port, Telnet, WEB Browser, SNMP
- Automatic mode switching between Driver and Raw Mode
- Supports TCP/IP, UDP, Telnet, DHCP, ICMP, HTTP, SNMP V1/2c/3, DNS

[Contact Online...](#)

NetCom 811

Quick Link: | [Features](#) | [More Pictures](#) | [Overview](#) | [Application](#) | [Hardware](#) | [Interface](#) | [Performance](#) | [Operating Modes](#) | [Power and Environment](#) | [Special Features](#) | [Security](#) | [Ordering Information](#) | [Optional Accessories](#) |

■ More Pictures



Klick on the thumbnails for the large picture ...

[>Back to top](#)

■ Overview

NetCom 811 is an industrial-strength network-based serial device server for connecting eight RS232 device like CNC, PLC, weighting scale, scanner and other devices directly to the 10/100Mbps Ethernet network running TCP/IP.

In addition to allowing serial devices to get networked, any host (PC Server or Workstation) without network access can also access remote serial device via adding NetCom devices to the existing serial port. NetCom 811 can be configured over Driver Panels, WEB Browser, serial Port, Telnet, SNMP and serves as a transparent serial channel without platform and distance limitation.

■ Application

- Industrial / Factory / Laboratory automation
- Automatic warehouse control system
- Wafer fabrication system
- Retail system
- SCADA system
- Building automation system
- Self-service banking system
- Other remote and distributed serial devices control

■ Hardware

Processor	ARM 7 TDMI 50MHz
I/O controller	16C550C or compatible
Memory	8MB SDRAM, 2 MB Flash
Connector type	RJ45 for LAN, DSUB 9 male for serial Port

[>Back to top](#)

■ Interface

LAN interface	Auto-detecting 10BaseT/100BaseTx
----------------------	----------------------------------

Protocols	TCP/IP, UDP, Telnet, DHCP, ICMP, HTTP, SNMP V1/2c/3, DNS
Serial interface	RS232
No. of port	8, Speed up to 460Kbps
Available Modes	RS232 full duplex
Signals	TxD,RxD, RTS,CTS, DTR,DSR, DCD, RI, GND

[>Back to top](#)

■ Performance

Speed	up to 460Kbps
Parity	None, even, odd, space, mark
Data bits	5, 6, 7, 8
Stop bits	1, 1.5, 2
IRQ	None
I/O address	None

[>Back to top](#)

■ Operating Modes

Driver mode	VScom Driver for Windows NT 4.0, 2000 up to 7, Server 2000 up to 2008 R2, both x86 and x64 Editions. The Driver creates a virtual Com port, using Vscom NetCom protocol.
TCP Raw Server	Raw data transfer over TCP/IP. Accepts multiple incoming connections.
TCP Raw Client	Raw data transfer over TCP/IP. Connects to multiple hosts or devices waiting for incoming connections.
TCP Advanced Settings	Special settings for user-defined modes
UDP Mode	Raw data transfer by UDP. The NetCom is client and server at the same time. With the timeout functionality and a configurable trigger string it can make defined UDP packets of incoming data.
Null Modem Tunnel	Connecting two NetCom used as virtual null modem cable.
IP Modem	The serial port emulates a standard modem. Operates by AT-commands, and dials to IP-Addresses instead of phone numbers. Windows "INF"-Driver provided for installation.
Print Server	The NetCom accepts print jobs, and spools them to the attached serial printer. Operates as of RFC1197, similar to the line printer daemon in Unix-systems

[>Back to top](#)

■ Power and Environment

Power requirements	9 - 30V DC, 600mA @ 12V, Terminal Block
Power supply Adapter	12V DC 1A
Dimension	167× 99×43 mm ³ (W×L×H) 189×102×44 mm ³ with DB9 connectors and ears
Operating Temp	0°C - 60°C
Storage Temp	-20°C - 85°C
Case	SECC sheet metal (1mm)
Weight	0.7kg

[>Back to top](#)

■ Special Features

Installation	Configuration utility automatically finds NetCom devices in the network
Operating mode	Automatic mode switching between Driver and TCP RAW mode. With TCP Advanced settings it is possible to configure the NetCom for using it in multiple modes, so it decides automatically which mode should be used.
Configuration	Configuration over Driver Panels, NetCom Manager, WEB Browser, serial console, Telnet, SNMP
SNMP	special VScom MIB included
ART	no
DNS	Domain Name Server support
Firewall	Special precautions for Firewall environments
Firmware	Firmware update over WEB Browser, Telnet, ComPort
LEDs	LEDs for Power, Tx, Rx, LAN Link, LAN Speed
>Back to top	
■ Security	
Password access	Every capabilities of configuration use the same password including SNMP V3
>Back to top	
■ Ordering Information	
Art.No	670
Product Name	NetCom 811
Packing list	NetCom 811 Power supply adapter 12V, 1A CD-ROM with Driver and configuration software Printed Quick Installation Guide
>Back to top	
■ Optional Accessories	
DK 35A	DIN-Rail mounting kit
Serial Adapter	Null-Modem adapter, change male to female
>Back to top	

NetCom 811

[>Back](#)

