

Model Information



■ Features

- Metal case
- DIN-Rail mountable
- RS232 2x DB62 female combi-ports
- Speed up to 500 kbps
- USB 2.0
- 9-30V DC power adapter

[Contact Online...](#)

VScom USB-16COM-M CBL

Quick Link: | [Features](#) | [More Pictures](#) | [Overview](#) | [Hardware Specifications](#) | [Ordering Information](#) |

■ More Pictures



Click on the thumbnails for the large picture ...

[>Back to top](#)

■ Overview

Serial ports on USB allow further use of existing devices, even when the computer doesn't offer serial ports.

The high speed serial port with the 128 byte FIFO allow high speed communication, even in heavy loaded systems. Unique features reduce the system load. The serial port also allows unusual speed settings like 500.000bps.

USB-16COM-M CBL uses a small case due to the high-density DB62 combi connectors for the serial ports. Mounted even in narrow environment, it connects to serial devices via an octopus cables or connection boxes.

■ Hardware Specifications

Serial interface

- 16 x RS232
- Connector 2 x DB62 female, Adapters available
- Speed up to 500 kbps
- Signals TxD, RxD, RTS, CTS, DTR, DSR, DCD, GND

USB Interface

USB 2.0

- Self powered
- External power supply 9-35V DC
- Connected by terminal block.
- Adapter 12V included.

Driver

- Windows 2000 to Windows 10 (x86 and x64)
- Windows Server 2000 to 20012 (x86 and x64)
- Linux (Kernel 2.6 built-in, 2.4 available)

[>Back to top](#)

■ Ordering Information

Part Number

653

Product Name

VScom USB-16COM-M CBL

Packing list

- VScom USB-16COM-M CBL Adapter
- USB cable 0,9m
- Power adapter

Optional Accessories

- [DK 35A](#) DIN-Rail mounting kit
- [DB62 to ...](#) Octopus cables and connection boxes

Dimensions

124×78×51 mm³ (W×D×H)

[>Back to top](#)



Option Octopus cable

[>Back](#)

