

Model Information



■ Features

- RS232/422/485 DB9 male ports
- Speed up to 3000 kbps
- no external power supply

[Contact Online...](#)

VScom USB-COM-I PLUS

Quick Link: | [Features](#) | [More Pictures](#) | [Overview](#) | [Hardware Specifications](#) | [Ordering Information](#) |

■ More Pictures



Click on the thumbnails for the large picture ...

[>Back to top](#)

■ Overview

Industrial serial ports on USB connect RS-422 and RS485 devices, used in industrial environment. With RS-485 the data direction is controlled by the port, without further action from the software. The high speed serial port with the 128 byte FIFO allow high speed communication, even in heavy loaded systems. Unique features reduce the system load. The serial port also allows unusual speed settings like 500.000bps.

■ Hardware Specifications

Serial interface

- 1 x RS232/422/485 configured by DIP switch
- Connector DB9 male

Speed

- RS232: up to 500kbps
- RS422: up to 3Mbps
- RS485: up to 3Mbps

Available Modes

- RS232 full duplex
- RS422 full duplex
- RS485 4-wire, full duplex
- RS485 2-wire, half duplex, with echo
- RS485 2-wire, half duplex, without echo

Signals

- RS422: Tx+/-, Rx+/-, RTS+/-, CTS+/-, GND
- RS485 4-wire: Tx+/-, Rx+/-, GND

- RS485 2-wire: Data+/-, GND

USB Interface

USB 2.0

- Bus powered
- No external power supply

Driver

- Windows 2000 to Windows 10 (x86 and x64)
- Windows Server 2000 to 20012 (x86 and x64)
- Also Windows 98/SE/ME.
- Linux (Kernel 2.6 built-in, 2.4 available)

[>Back to top](#)

■ Ordering Information

Part Number

631

Product Name

VScom USB-COM-I PLUS

Packing list

- VScom USB-COM-I PLUS Adapter
- USB cable 0,25m integrated

[>Back to top](#)

VScom USB-COM-I PLUS

[>Back](#)

