



E-COM 19"-GIGABIT SWITCH UNMANAGED

48X10/100TX + COMBO: 2X10/100/1000T + 2X1000SFP

IEEE Standard	IEEE 802.3 10BASE-T IEEE 802.3u 100BASE-TX IEEE 802.3ab 1000Base-T IEEE 802.3z Gigabit fiber IEEE 802.3x Flow control and Backpressure
Connector	100Base-T: 48 x RJ-45 Gigabit copper: 2 x RJ-45 MINI GBIC: 2 x MINI GBIC socket
Switch Architecture	Store and forward switch architecture. Back-plane up to 20 Gbps
MAC Address	8K MAC address table with auto learning function
Packet Buffer	7 Mbits for packet buffer
LED	System power (green) 10/100TX Port: Link / Activity (green), Collision (yellow) Gigabit copper port: Link / Activity (green), Speed (yellow) MINI GBIC: Link / Activity (green)
Power	AC 100 – 240 V, 50 / 60 Hz
Power Consumption	25 Watts @ AC 110 V
Ventilation	Fan: 1 unit
Operating Environment	0 – 45 °C, 5 % – 95 % RH
Storage Environment	-40 °C – 70 °C, 95 % RH
Dimension	440 mm (W) x 225 mm (D) x 44 mm (H)
EMI	FCC Class A, CE
Safety	UL, cUL, CE/EN60950

Part Number	Description
261000800	UL, cUL, CE/EN60950

Headquarters // eks Engel GmbH & Co. KG
Schuetzenstrasse 2-4 // 57482 Wenden, Germany
Tel. +49 2762 9313-600 // Fax +49 2762 9313-7906
info@eks-engel.de // www.eks-engel.de

North America // eks Fiber Optics LP
150 N Michigan Ave, Suite 2818
Chicago, IL 60601, USA // Tel. +1 (312) 291-4482
info@eks-fo.com // www.eks-fo.com

eks fiber optic systems