



FIMP-S

INDUSTRIAL COMPACT SPLICEBOX With 120mm x 32mm x 120mm, our industrial splice box FIMP-S is by far smaller than comparable 19" solutions. Its inner values are really convincing as well so that the installation is quite simple and done very fast. FIMP is ready for splicing and contains splice tray, couplings, pigtails and cable gland. Regarding different couplings, you can choose from ST, SC, LC and E-2000. The splice cassette can be removed for splicing and since the cassette is magnetizable, it can easily be fixed onto a splice unit. The cassette has got a hole for splice units with a bolt.

The powder coated stainless steel housing is also magnetizable so that the splice box can easily be affixed to another housing or to a switch cabinet in case of no different tray. Furthermore, FIMP has got a clip for DIN rail mounting (35mm) and optional a kit for wall fastening. Thus, there are space-saving and flexible solutions for mounting our FIMP.





Туре ММ	6xST Duplex 62MM	6xSC Duplex 62MM	3xLC Quattro 62MM	6xE2000 Duplex 62MM	6xST Duplex 50MM	6xSC Duplex 50MM	3xLC Quattro 50MM	6xE2000 Duplex 50MM	
Article no.	06300 22196-00	06300 22396-00	06300 22493-00	06300 22596-00	06300 12196-00	06300 12396-00	06300 12493-00	06300 12596-00	
Type SM	6xST Duplex	6xSC Duplex	6xSC 8° APC Duplex	3xLC Quattro	6xE2000 Duplex	6xE2000 8° APC Duplex			
Article no.	06300 36196-00	06300 36396-00	06300 38396-00	06300 36493-00	06300 36596-00	06300 38596-00			
Weight	380 g								
Dimensions	Height: 120 mm; Width: 32 mm; Depth: 120 mm								
Operating Temperature	-40 °C − +75 °C								
Humidity	10% – 95% relative, non condensing								
Housing				Steels	sheet, powder	coated			
Accessories	Article no.		Description						
	0600E90001		Cable gland M20						
	0600E90002		Nut M20						
	0600E90003		Strain relief						
	0600E9000	7	Splice holde	r					
	0600E90008	3	Splice prote	ction					
	0600E90009	9	Cable tie						
	0600E90013	3	Dual Mount	Kit					