

Model Information



■ Features

- Metal case
- DIN-Rail mountable
- RS232 DB9 male port
- Speed up to 500 kbps
- no external power supply

[Contact Online...](#)

VScom USB-2COM-M

Quick Link: | [Features](#) | [More Pictures](#) | [Overview](#) | [Hardware Specifications](#) | [Ordering Information](#) |

■ More Pictures



Click on the thumbnails for the large picture ...

[>Back to top](#)

■ Overview

Serial ports on USB allow further use of existing devices, even when the computer doesn't offer serial ports.

The high speed serial port with the 128 byte FIFO allow high speed communication, even in heavy loaded systems. Unique features reduce the system load. The serial port also allows unusual speed settings like 500.000bps.

■ Hardware Specifications

Serial interface

- 2 x RS232
- Connector 2 x DB9 male
- Speed up to 500 kbps
- Signals TxD, RxD, RTS, CTS, DTR, DSR, DCD, GND

USB Interface

- USB 2.0
- Bus powered
 - No external power supply

Driver

- Windows 2000 to Windows 10 (x86 and x64)
- Windows Server 2000 to 20012 (x86 and x64)
- Linux (Kernel 2.6 built-in, 2.4 available)

[>Back to top](#)

■ Ordering Information

Part Number

642

Product Name

VScom USB-2COM-M

Packing list

- VScom USB-2COM-M Adapter

Optional Accessories

- USB cable 0,9m
- [DK 35A](#) DIN-Rail mounting kit
- [9PF-9PF](#) RS232 Null-Modem adapter, change male to female

Dimensions

- 57×72×22 mm³ (W×L×H)
- 82×82×22 mm³ with DB9 connector and ears

[>Back to top](#)

VScom USB-2COM-M

[>Back](#)

