

Universal serial RS232/RS422/RS485 to multimode optic fiber media converter



RD300-OF

PLUG & PLAY



RD300-OFR

- 3 in 1 built-in serial interface : RS232/RS422/RS485
- Serial link up to 2 Mbps for RS422 & RS485 mode, 1 Mbps for RS232 mode
- Reliable error free communication even in case of EMI/RFI perturbations
- Fiber length up to 5000 m (100/140 μ m fiber type), ST type connectors
- Automatic RS485 line turn-around, software independent
- Half-duplex & Full-duplex bidirectional data transmission
- Activity LED for fiber and copper TxD & RxD signals, error LED in case of fiber breakdown
- Wide DC power range, from +9VDC to +36VDC
- Point to point mode and multipoint redundant mode (fault tolerant for the RD300-OFR model)
- 15 KV ESD protection and HF filtering on the copper side
- Robust & compact metal case, **CE** industrial grade, cabinet or 35 mm Din Rail mounting

RD300-OF & RD300-OFR

Multimode fiber optic media converter



5-YEAR WARRANTY

Using fiber optic enables to use a higher communication bandwidth while offering a total immunity against EMI/RFI interferences and an increased security as well.

The optical fibre still offers other advantages : use without risk in an explosive environment, no EMC emission, no ground loops, immunity against lightning and high voltage environments, they are finally lighter, less cumbersome, inert and corrosion resistant ...

Plug & Play : The RD300-OF device features a self configuration mechanism based on a CPLD component freed you from the tiresome operation which consist in the serial parameters setup, product is "Plug & Play".

RD300-OF features in standard a built-in system to control the fiber integrity, it reports automatically any failure with an error LED and also setup a relay contact (MOSFET) to activate any external safety device.

Its small size, design features and its great adaptability make the RD300-OFR a really universal product capable to satisfy to major needs of the industry.



TECHNICAL CHARACTERISTICS

Conversion	Serial RS232/RS422/RS485 to multimode fiber optic, RS485 mode self line turnaround
Serial speed	2Mbps for RS422/RS485 mode, 1Mbps for RS232 mode
Distance	5000m with a 100/140 µm fiber type at 25°C
Serial protocols	The device supports any kind of communication protocols (Modbus, Unitelway, Profibus, DH+ and any ASCII or binary serial protocols ...).
Configuration	Serial link parameters auto configuration, no switches. Line polarization, termination and selection between RS232/RS422/RS485 modes are configurable by mini-switches.
Serial connectors	Pluggable screw-in terminal, TxD & RxD signal for RS232 mode, TxA, RxA, TxB, RxB for RS422 mode, TRxA & TRxB for RS485 mode.
Optic fiber	50/125 µm, 62.5/125 µm, 100/140 µm & 200 µm fiber support, 820 nm wave length, selectable ON/OFF state of the fiber light at the idle state.
Power budget	Power budget : 22.4 dB, 5 dB & 11 dB attenuator for short distance communication
Fiber connectors	2 ST type connectors for the RD300-OF model, 4 for the RD300-OFR model
Network topologies	Point to point, ring, single-master & dual-master ⁽¹⁾ , redundant fiber ring ⁽¹⁾ , dual ring & dual master ⁽¹⁾ , dual point to point ⁽¹⁾ , start ⁽¹⁾ depending to models, see note ⁽¹⁾ .
Signalling	4 LEDs for TxD & RxD signals on both copper and fiber optic side, 1 LED for power, 1 error LED for fiber breakdown for the RD300-OF model, 3 additional LEDs on the RD300-OFR model for TxD, RxD signals and fiber error.
Fan-out	31 RS485 interfaces, 10 RS422 interfaces, input load 1/8 UL in RS485 mode
EMI/RFI protection	Built-in continuous line surge protection, ESD protection (15 KVeFF), HF filtering
Isolation	Infinite galvanic isolation through the optic fiber
CEM	NF EN 55022 residential emission, NF EN 61000-6-2 industrial immunity
Security	Fiber breakdown self diagnostic, failure is reported on a LED and a relay contact (MOSFET) is activated.
Power supply	+9VDC to +36VDC (pluggable screw-in terminal), 2.1W for RD300-OF, 2.3W for RD300-OFR
Environnement	Temperature from -5°C to +65°C, storage -40°C to +80°C, relative humidity from 0 to 95% RH without condensation.
Dimensions, weight	107 mm (L) x 88 mm (W) x 25 mm (H), 260 g

⁽¹⁾ These features are available only with the RD300-OFR device

References to order

RD300-OF	Serial RS232/RS422/RS485 to multimode fiber optic media converter, +9VDC to +36VDC power supply, din rail mounting
RD300-OFR	Serial RS232/RS422/RS485 to multimode fiber optic media converter, multipoint & fault tolerant, +9VDC to +36VDC power supply, din rail mounting

All the brand names mentioned in this document are trademarks. ACKSYS is constantly looking at ways to improve its products. The current specifications may therefore be modified without notice and the characteristics set out herein should not be construed as creating any contractual obligation. All the products featured herein are designed and manufactured in Europe.