

EcoPanel 70

Quick-loading images, an extensive symbol library, user-friendly, high-performance visualisation software free of charge in extremely compact dimensions make this panel unique in the entry-level colour-touch applications in the low-cost segment.

Additional possibilities for archiving and assigning or allocating to the S7 world are available in the Ethernet version.



General

• Power supply unit:	24 V DC (18 - 36 V DC)
• Dimensions:	180 x 135 x 50 mm (W x H x D)
• Cut-out dimensions:	163 x 118 mm
• Weight:	800 g
• Operating temperature range:	0 ... +50° C
• Storage/transportation temperature range:	-20 ... +70° C
• Humidity:	25 - 85 % humidity
• CE certification:	according to EN 61000-6-2 and EN 61000-6-4
• Place of manufacture:	Made in Germany
• Protection class:	IP65 frontally

Panel

• Configurable with QUICKMENU 5 (see reverse)
• Display: 5.7" STN QVGA colour LCD, resolution: 320 x 240 pixels with 256 colours
• Touch: resistive Touch
• Background lighting: CCFL
• Typical backlight service life at 25° C: 40.000 hours (shelf life)
• Contrast setting: Software
• 960 KB battery-backed virtual memory for visualisation project data
• 2 serial interfaces for configuration and connection to the Berthel control system
• SD/MMC slot for external memory up to 4GB for trend and message archiving
• Input format: alphanumeric via virtual keypad

Communication / protocols

Ethernet:

- Ethernet interface for configuration and connection to Berthel control systems and to all S7 control systems via RFC1006

QUICKMENU 5 “the S7 visualisation”

You can expect a modern, ergonomic visualisation tool, optimally attuned to the selected target device. The configuring philosophy uses the most successful commercial graphic development environments as reference. Without causing an overload, maximum functionality and operating comfort is provided. You will quickly recognise the coherencies in the


typical examples. Designing the visualisation function becomes a pleasure, intuitively operable and self-explanatory.

Try it out yourself, also without target device with integrated simulator. A full version is available on the internet free of charge.

Tree view

The tree view is the central platform/hub for all objects. You navigate via it to the elements and objects to be configured.

Here you configure languages, texts, trends, formulas, screen displays, etc. With a few clicks these are again brought to the surface for processing.



Baumansicht

Image view

Creating the templates is the easiest of procedures. A tool bar provides you with all the objects for the selected target device. After selecting an object “drag it onto the example: project image trend desktop” and complete the dialogue pages offered. You can find all created objects again in the tree view.



Example: Project image building automation

Parameter view


The fine adjustment for the selected object is done in the parameter view. For that purpose an online help function guides you with extensive explanations and configuration possibilities. A user manual is completely superfluous.



Parameter view

Simulator / Viewer

Run your created project on the PC. Set the PLC variables at your own discretion, start trends, set off the alarms, animate the bar graphs and progress indicators. Start the archiving and view the result of the recording or use the simulator as “viewer” for recorded production data.



Project image in the simulator

Technical data

• Executable under:	WINDOWS®2000 / XP / VISTA
• Character set:	UNICODE-16
• Languages:	multilingual, no limitations
• Variable format:	S7 300 compatible
• Number of variables:	no limitation
• Dynamic texts:	no limitation
• Malfunction message system:	integrated
• Alarm messages:	100 (battery-backed)
• Incident messages:	100
• Alarm and messages archive / messages archive viewer:	up to 4GB (recording possible over years)
• Trending system:	4 trends each with 8 channels in different formats
• Trend archiving:	up to 4GB (recording possible over years)
• Formula management:	256 formulas, 1024 records, 256 variables/formula
• Password management:	10 password levels
• Bar graph / progress indicator:	integrated
• Radio buttons, check boxes:	integrated
• Buttons, images and image lists:	integrated
• Image formats:	vector graphics and bitmaps (wmf, jpeg, bmp...)
• Project data produced:	DBs in S7 300 compatible WDL format
• Project simulation:	integrated

Technische Daten

• Languages, text import/export:	integrated
• Import of S7 symbol files:	integrated
• Online functions:	upload / general reset (serial or via Ethernet)
• Online help:	German / English
• User interface, language:	German / English

Special features

• STEP 7® compatible
• No licensing costs connected to Berthel control systems and panels
• Very short training period
• Produces extremely compact project data
• Can be combined with STEP 7® projects and transferred with the STEP 7® project (from QIII / 2008)
• Can be applied in connection with every S7 control system as a visualisation tool
• Remote visualisation with Visual Agent from Berthel possible via router / Internet
• Extremely low use of system resources
• Very short development cycles
• Minimal installation effort / outlay
• Industrial vector graphics library included as DEMO
• Integrated simulator

Special requests?

Berthel already makes economic solutions specified by client for their special requirements in case of small ranges possible. Send your request for a concept free of charge!