

# /// CONTROLNET PCI INTERFACE CARD ///

## Overview

The SST ControlNet interface card connects your PCI bus computer to ControlNet.

## Applications

Many third party software programs support the SST ControlNet interface card for various applications including:

- Operator Interface/HMI/SCADA
- PC Control
- Network Configuration, Troubleshooting and Diagnostics
- PLC Programming

## Features

- *High performance*
  - 32-bit i960 RISC CPU
  - Simultaneous operation of 128 scheduled and 128 unscheduled message screeners
  - Simultaneous functionality of ControlNet messaging, scanner and adapter
- *Ease of Use*
  - Designed to work with any existing SST 5136-SD DH+ software driver for Operator Interface and HMI applications
  - Works with Rockwell Software's RSLinx allowing compatibility with Rockwell's "RS" family of products
  - Integrated configuration tool included for ControlNet scanner applications

## Custom Driver Development

SST provides an open documented memory map interface with example C source code and Windows 32-Bit DLLs and drivers.



### *Included with SST ControlNet PCI Interface Card*

- ControlNet Network Capture Tool
- ControlNet Configuration Tool
- ControlNet Network Analyzer
- Microsoft Windows NT drivers/DLLs
- Rockwell Software RSLinx Support
- Example code and open memory map interface for custom driver development
- OPC Server
- 24/7 Global Technical Support



Network Interface Cards

[www.mySST.com](http://www.mySST.com)

Distribución: **ER-SOFT, S.A.** Email: [er@er-soft.com](mailto:er@er-soft.com), Tel: +34 916 408 408

## Hardware Specifications

- 32 bit, short card (see PCI specification), surface-mount technology PCI interface card
- PCI specification 2.1 compliant
- Intel i960 32-bit RISC 33 Mhz processor
- 1 Mbyte local 32-bit RAM
- 1 Mbyte of shared 32-bit RAM
- 1 Mbyte of Flash memory
- Standard ControlNet LEDs for each channel
- LAN Controller (no ControlNet ASICs used) is implemented in a field programmable gate array (FPGA)
  - FPGA executes all protocol activity, including scanning I/O, without intervention from i960 processor
  - FPGA is software field upgradeable
- Network Interface
  - 2 BNC connectors
  - ControlNet redundancy implemented in hardware on interface card
  - Isolated Network Access Port (NAP)
- 5136-SD DH+ Emulation
  - Supports standard PCCC messaging
  - Applications using interrupts may require minor changes
- Power requirements: 750 mA @ 5 V
- Operational temperature: 0 to 50C (32 to 122°F)
- Storage temperature: -25 to 70C (-13 to 158°F)

## Other Reference Materials

### Web Site

- [www.mySST.com/cards/controlnet/cnet.asp](http://www.mySST.com/cards/controlnet/cnet.asp)

### Related ControlNet Products

- Network Interface Cards connect various computer bus formats to industrial networks
- Network Diagnostic and Configuration Software
- Network Gateways
- Data Servers include OPC and DDE Servers

### Certifications

- ControlNet Conformance Tested

### Affiliations

- Active member of ControlNet International

### Ordering Information

- Order part number 5136-CN-PCI

[www.mySST.com](http://www.mySST.com)

## Also available from SST:

Gateways  
PLC Modules  
Data Servers  
Interface Cards  
Embedded Solutions  
I/O Simulation Software  
Diagnostic and Configuration Software

ECNPCI

May 2003

50 Northland Road  
Waterloo, Ontario  
Canada N2V 1N3  
Tel: 519-725-5136  
Fax: 519-725-1515

43 rue Mazagran  
76320 Caudebec-lès-Elbeuf  
France  
Tel: +33-2-32-96-04-20  
Fax: +33-2-32-96-04-219

Landmark Tower 43F  
Minatomirai 2-2-1, Nishi-ku  
Yokohama-city 220-8143 Japan  
Tel: +81-4-5224-3560  
Fax: +81-4-5224-3561

**W Woodhead Connectivity**  
applicom • Brad Harrison • mPm • NetAlert • RJ-Link • SST  
THE GLOBAL LEADER IN INDUSTRIAL COMMUNICATIONS AND CONNECTIVITY

SST is a division of Woodhead Canada Limited. PICS Simulation and X-Link are registered trademarks of Woodhead Canada Limited.  
SST is a trademark of W

Distribución: **ER-SOFT, S.A.** Email: [er@er-soft.com](mailto:er@er-soft.com), Tel: +34 916 408 408