

48x10/100/1000TX + + COMBI: 2x10/100/1000T + 2x1000SFP Gigabit Ethernet Switch



Benefits

| | |
|---|--|
| ■ 48-port 10/100TX plus 2 10/100/1000T, 2 Mini GBIC | ■ Switch fabric up to 20Gbps / Non-blocking architecture |
| ■ Confirms to IEEE802.3 10BASE-T, 802.3u 100BASE-TX and IEEE 802.3ab 1000Base-T | ■ IEEE802.3x Flow control |
| ■ 19" rack mount design | ■ 4 x Gigabit uplink port |

Hardware Specification

| | |
|-----------------------|--|
| Standard | IEEE802.3 10BASE-T IEEE802.3u 100BASE-TX IEEE802.3ab 1000Base-T IEEE802.3z Gigabit fiber IEEE802.3x Flow control and Back pressure |
| Connector | 100Base-T: 48 x RJ-45 Gigabit copper: 2 x RJ-45 MINI GBIC: 2 x MINI GBIC socket |
| Switch architecture | Store and forward switch architecture. Back-plane up to 20Gbps |
| MAC address | 8K MAC address table with auto learning function |
| Packet buffer | 7Mbits for packet buffer |
| LED | System power (Green) 10/100TX Port: Link/Activity (Green), Collision (Yellow) Gigabit copper port: Link/Activity (Green), Speed (Yellow) MINI GBIC: Link/Activity (Green) |
| Power | AC 100~240V, 50/60Hz |
| Power consumption | 25 Watt @ AC 110V |
| Ventilation | Fan: 1 pc |
| Operating environment | 0°C~45°C, 5%~95%RH |
| Storage environment | -40°C~70°C, 95% RH |
| Dimension | 440mm(W) x 225mm(D) x 44mm(H) |
| EMI | FCC Class A, CE |
| Safety | UL, cUL, CE/EN60950 |

Order Information

| Part Number | Product Family | Description |
|-------------|----------------|--------------------------------|
| 26 1000 800 | DragonLine | 48x10/100TX + 4xGigabit Uplink |