

## 4x10/100TX + 2x100FX Industrial Ethernet Switch (Slimline)



### Benefits

<ul style="list-style-type: none"> <li>■ System Interface/Performance           <ul style="list-style-type: none"> <li>➢ RJ-45 port support Auto MDI/MDI-X Function</li> <li>➢ Store-and-Forward Switching Architecture</li> <li>➢ Back-plane (Switching Fabric): 1.2Gbps</li> <li>➢ 448Kbits Memory Buffer</li> <li>➢ 2K MAC Address Table</li> </ul> </li> </ul>	<ul style="list-style-type: none"> <li>■ Case/Installation           <ul style="list-style-type: none"> <li>➢ IP-30 Protection</li> <li>➢ DIN Rail and Wall Mount Design</li> </ul> </li> </ul>
<ul style="list-style-type: none"> <li>■ Power Supply           <ul style="list-style-type: none"> <li>➢ Wide-range Redundant Power Design</li> <li>➢ Power Polarity Reverse Protect</li> <li>➢ Overload Current Re-settable Fuse Present</li> </ul> </li> </ul>	<ul style="list-style-type: none"> <li>■ Provides EFT protection 3000 VDC for power line</li> </ul>
<ul style="list-style-type: none"> <li>■ Provides broadcast storm protection</li> </ul>	<ul style="list-style-type: none"> <li>■ Supports 6000 VDC Ethernet ESD protection</li> </ul>

### Standard Compliance

IEEE Standard	IEEE 802.3 10Base-T Ethernet IEEE 802.3u 100Base-TX and 100Base-FX Fast Ethernet IEEE 802.3x Flow Control and Back Pressure
---------------	---

### Hardware Specification

Switch Architecture	Back-plane (Switching Fabric): 1.2Gbps Packet throughput ability (Full-Duplex): 1.488Mpps @64bytes
Transfer Rate	14,880pps for Ethernet port 148,800pps for Fast Ethernet port
Memory Buffer	448Kbits
MAC Address	2K
Connector	10/100TX: 4 x RJ-45 with auto MDI/MDI-X function 100M fiber: 2 x SC type connector for Singlemode or Multimode type fiber cable 10Base-T: 2-pair UTP/STP Cat. 3, 4, 5 cable
Network Cable	EIA/TIA-568 100-ohm (100m) 100Base-TX: 2-pair UTP/STP Cat. 5 cable EIA/TIA-568 100-ohm (100m)
Optical Cable	Multimode: 50/125µm~62.5/125µm Singlemode: 9/125µm Available distance: 2km (Multimode) / 30km (Singlemode) Wavelength: 1310nm (Multimode/Singlemode)
Protocol	CSMA/CD
LED	Per port: Link/Activity (Green), Full duplex/Collision (Yellow) Per unit: Power 1 (Green), Power 2 (Green), Fault(Red)
Reserve polarity protection	Present

Overload current protection	Present
Power Supply	DC 12~48V Redundant power with polarity reverse protect function and removable terminal block
Power Consumption	6.41 Watt
Operating Humidity	5%~95% (Non-condensing)
Operating Temperature	Standard: -10°C~60°C
Storage Temperature	-40°C~85°C
Case Dimension	Metal case. IP-30, 30mm (W) x 95mm (D) x 140mm (H)
Installation	DIN Rail and Wall Mount Design
EMI	FCC Class A, CE EN61000-4-2 (ESD), CE EN61000-4-3 (RS), CE EN-61000-4-4 (EFT), CE EN61000-4-5 (Surge), CE EN61000-4-6 (CS), CE EN61000-4-8, CE EN61000-4-11, CE EN61000-4-12, CE EN61000-6-2, CE EN61000-6-4
Safety	UL, cUL, CE/EN60950-1
Stability Testing	IEC60068-2-32 (Free fall), IEC60068-2-27 (Shock), IEC60068-2-6 (Vibration)

### Order Information

Part Number	Product Family	Description
26 470 202	DragonLine	4x10/100TX + 2x100FX (SC/MM/2km) Industrial Ethernet Switch
26 470 202E	DragonLine	4x10/100TX + 2x100FX (SC/MM/2km) Industrial Ethernet Switch Wide Operating Temperature (-40°C~+75°C)
26 470 252	DragonLine	4x10/100TX + 2x100FX (SC/SM/30km) Industrial Ethernet Switch
26 470 252E	DragonLine	4x10/100TX + 2x100FX (SC/SM/30km) Industrial Ethernet Switch Wide Operating Temperature (-40°C~+75°C)