VX-60F / VX-80F



The **VX-60F** and **VX-80F** are totally fanless Panel PCs with the CPU board specifically designed for industrial needs and with availability guaranteed overtime. In the compact design you will find serial ports, LPT, Ethernet, PS/2 and the increasingly used USB ports.



TECHNICAL SPECIFICATIONS

PROCESSOR	Intel Celeron M 600 MHz – 512KB cache	FRONTAL PROTECTION	IP65
MEMORY	256MB ÷ 1GB	MOUNTING	Panel Mounting
DISPLAY LCD	VX-60F: Colour TFT – 6.5" (VGA 640x480)	POWER SUPPLY	24 V/DC
	- 400cd/sm		
	VX-80F: Colour TFT – 8.4" (SVGA 800x600)		
	- 400cd/sm	DIMENSION (mm) WxHxD	VX-60F: 217x176x75
TOUCH SCREEN	4 wire resistive		VX-80F: 248x207x75
INTERFACES	K/M PS2, 3x RS-232, 4x + 1x USB 2.0,	OPERATING SYSTEM	Windows XP PRO
	Ethernet 10/100, VGA, Audio, Parallel (opt.)		Windows XP Embedded
SL0T	PC 104 PCI (n.a. with HD)		
SSD FLASH DISK	C.F. Type II socket	OPERATING TEMPERATURE	0° ÷ 45°C
HARD DISK	2.5" - PATA	RELATIVE HUMIDITY	10% ÷ 90% Non condensing



VX-60F / VX-80F

It can be equipped with a Hard Disk, for applications that need the typical functions of a complete operating system or with a Compact Flash that allows embedded operating systems such as Windows XPE or Linux.









4x USB on the connector side and 1x USB on the front panel in addition to 1x Ethernet port allow connection to a vast array of devices.