

VX-150P / VX-151P



The **VX-150P** and **VX-151P** are panel PCs with high brightness 15" TFT displays, extremely compact, mainly intended for XP Embedded applications.

The three model options of Single Board Computer use different processors, allowing for a complete choice that can meet every need in the industrial or building sector.

TECHNICAL SPECIFICATIONS

PROCESSOR	Intel Celeron M 600MHz: 400 MHz; Celeron/Pentium M 400/533 MHz; Core Duo: 667/533 MHz	FRONTAL PROTECTION	IP65
MEMORY	256MB ÷ 2GB	MOUNTING	Panel Mounting
DISPLAY LCD	Colour TFT – 15" XGA 1024x768 - 350cd/sm	POWER SUPPLY	115/230 V/AC (24V/DC opt)
TOUCH SCREEN	8 wire resistive	DIMENSION (mm) WxHxD	VX-150P: 388x316x87 VX-151P: 388x316x108
INTERFACES	2x K/M PS2, 3x RS-232, 4x + 1x USB 2.0, 2x Ethernet 10/100 (Celeron/ Pentium M) 2x Ethernet 10/100/1000 (Core Duo), VGA, Audio, Parallel (only for VX-151P with Celeron/Pentium M)	OPERATING SYSTEM	Windows XP Professional Windows XP Embedded
SLOT	VX-150P: 1 mini-PCI (NOT with Core Duo); VX-151P: 1 PCI Half Size + 1 mini-PCI (NOT with Core Duo)	OPERATING TEMPERATURE	0° ÷ 45°C
SSD FLASH DISK	C.F. Type II socket	RELATIVE HUMIDITY	10% ÷ 90% Non condensing
HARD DISK	2.5" - Celeron/Pentium M: IDE PATA; Core Duo SATA/IDE PATA		

