

## VX-170P / VX-171P



**VX-170P** and **VX-171P** are panel PCs with high brightness 17" TFT display, extremely compact, mainly intended for XP Embedded applications. The three model options of Single Board Computer use different processors, allowing for a complete choice that can meet every need in the industrial or building sector.

### TECHNICAL SPECIFICATIONS

<b>PROCESSOR</b>	Intel Celeron M 600MHz: 400 MHz; Celeron/Pentium M 400/533 MHz; Core Duo: 667/533 MHz	<b>FRONTAL PROTECTION</b>	IP65
<b>MEMORY</b>	256MB ÷ 2GB	<b>MOUNTING</b>	Panel Mounting
<b>DISPLAY LCD</b>	Colour TFT – 17" (SXGA 1280x1024) - 300cd/sm	<b>POWER SUPPLY</b>	115/230 V/AC (24V/DC opt)
<b>TOUCH SCREEN</b>	8 wire resistive	<b>DIMENSION (mm) WxHxD</b>	VX-170P: 430x375x92 VX-171P: 430x375x113
<b>INTERFACES</b>	2x K/M PS2, 3x RS-232, 4x + 1x USB 2.0, 2x Ethernet 10/100 (Celeron/Pentium M) 2x Ethernet 10/100/1000 (Core Duo), VGA, Audio, Parallel (only for VX-171P with Celeron/Pentium M)	<b>OPERATING SYSTEM</b>	Windows XP Professional Windows XP Embedded
<b>SLOT</b>	VX-170P: 1 mini-PCI (NOT with Core Duo); VX-171P: 1 PCI Half Size + 1 mini-PCI (NOT with Core Duo)	<b>OPERATING TEMPERATURE</b>	0° ÷ 45°C
<b>SSD FLASH DISK</b>	C.F. Type II socket	<b>RELATIVE HUMIDITY</b>	10% ÷ 90% Non condensing
<b>HARD DISK</b>	2.5" - Celeron/Pentium M: IDE PATA; Core Duo SATA/IDE PATA		

