



Flytech Technology Co., Ltd.

No 168, Sing-ai Rd., Neihu District, Taipei City 114, Taiwan.

Tel: +886.2.8791-4988 Ext. 4800 Fax: +886.2.8791-4966

K780 (8.4" panel pc)



Model	Specification Description
K780/C36	System Motherboard: C36 CPU: Intel Atom N270 1.6GHz 512KB L2 cache FSB 533MHz Chip: Intel 945GSE + ICH7M Cooling: Fanless RAM: 1 x 512MB DDRII SO-DIMM (default) 100 x 100 mm VESA mounting holes. Aluminum housing
	LCD / Touch Panel Panel: K-784: 8.4" TFT LCD, 250 nits, 800 x 600 Touch: 4-wired Resistive type
	Storage 2.5" 80GB SATA Hard disk drive or SATA DOM (either one option)
	Power External 65W / 19V power brick
	External I/O 4 x RS-232 RJ45 Ports (two powered 5V or 12V selected by jumper) 4 x USB 2.0 Ports 1 x 10/100/1000 Base-T LAN (RJ45) 1 x RJ11 Cash Drawer Connector (12V or 24V) 1 x 2 nd VGA 1 x DC Jack latched
	Accessories 1 x Driver Bank & Manual CD disk 1 x Power cord
	Dimension / weight K-784 225 x175 x 55 mm; 1.8kg
	Environment EMC & Safety: CE,FCC Class A, LVD Operation temperature: 0~35C Storage temperature: -20C ~55C Operating & Storage Humidity: 5% ~90% RH, Non-condensing Water & Dust Proof: IP54 / NEMA 3 for display front only