



Anybus RemoteCom Ethernet / Web Metal version enables remote management of industrial devices and machinery from a standard web browser. RemoteCom is an easy-to-use web gateway which acts as a Modbus bridge and gives remote access and control of serial devices over Ethernet, Internet, LANs, and telephone modems. The metal version is designed for harsh industrial environments and fixed wall mounting.

#### Alarm management

RemoteCom contains built-in features for alarm handling. RemoteCom can send alarm messages with email, SMS or SNMP directly to authorized service personnel. Alarm conditions and trigger levels are easily configured via the built-in web interface

#### Visualization and Diagnostics

RemoteCom can gather and present live and historical logged data from connected devices. The built-in web server presents the data in the form of visual trend graphs. It is also possible to send the logged files (.csv) via FTP or E-mail.















#### Remote Control

RemoteCom also provides the ability to remotely control devices. RemoteCom enables authorized users, via the web interface to select and modify device parameters such as, target values or operation mode.

#### Online management server extends your functionality

As an additional service, a secure online management server is available that expands the functionality of Anybus RemoteCom. A basic online service is included with the Anybus RemoteCom unit and more advanced services can be ordered separately.

Please contact your local sales office or Anybus distributor for more information about the services available with the online management server.

KEY FEATURES	
	Communication over Ethernet, Internet, LAN's or telephone modems
	Alarm management by email, SMS or SNMP (Max 64 alarm parameters)
	Alarm history accessible via the built-in web server
	Built-in acquisition logger and trend graphs
	Web based configuration. No Windows tools or HTML editors needed
	Supports transparent bridging of Modbus data
	Serial protocols: Modbus RTU, Modbus ASCII, (master operation)
	Ethernet protocols: Modbus TCP master/slave, HTTP, SMTP (Email), FTP, Telnet, SNMP, DHCP
	RS-232 interface with full hardware modem control signals
	Ethernet 10/100 Mbit/s
	2x onboard digital inputs (24V)
	Multi language web interface (English, Swedish, German, French, Spanish are pre-installed)
	No licenses or royalties
	Online central management server for extended functionality

TECHNICAL SPECIFICATIONS	
<b>Size:</b>	92 mm x 115 mm x 25 mm
<b>Power Supply:</b>	9-28V DC
<b>Temperature:</b>	-40 to +85°C
<b>Current Consump:</b>	2W
<b>Baud Rate:</b>	10-100 Mbit/s
<b>Mech Rating:</b>	IP20
<b>Humidity:</b>	5-93% RH, non condensing
<b>Mounting:</b>	Wall mounted
<b>Certification:</b>	CE marked, UL pending
<b>Environmental:</b>	RoHS compliance
<b>Order Code:</b>	AB7706