



The Anybus X-gateway copies I/O-data in both directions thus enabling data exchange between the two networks. Default I/O configuration is 20 bytes Input and 20 bytes Output. Changing default settings is very simple and is carried out using the RS232 configuration port and a standard terminal interface on a PC, such as Hyper Terminal for Windows.

The Anybus-M AS-Interface Master module supports up to 62 slaves with a maximum of 248 digital input, 186 output signals. All standard services are available including detailed diagnostics. The network interface is optically isolated and equipped with a 2 pin pluggable screw connector. The Master supports intelligent auto-configuration or manual configuration via terminal program such as Hyper Terminal for Windows.

The AS-interface module is certified by the AS Interface user organization and has proven conformance and interoperability with leading manufacturers of I/O, sensors, valves etc.

The FIPIO interface is based an embedded AnyBus-S module providing industrial performance and quality. FIPIO station address can be selected via switches on the end side of the module. A transformer connection on the module provides a isolated fieldbus interface.

KEY FEATURES

- Manages control of up to 62 AS-Interface slaves
- 248 digital inputs and 186 digital outputs
- Supporting AS-Interface version 2.1 (compatible to version 2.0)
- Intelligent auto configuration support
- Supports both FIP and WorldFIP standards
- FIPIO profile FEDP (Extended Device Profile), class 0
- Transformer isolated FIP interface

TECHNICAL SPECIFICATIONS

Size:	126 mm x 110 mm x 42 mm
Power Supply:	24 VDC (±10%)
Temperature:	0-65°C
Current Consump:	max 300 mA
I/O Input:	Default 20 bytes, max 64 bytes (248 digital inputs on ASI)
I/O Output:	Default 20 bytes, max 64 bytes (186 digital outputs on ASI)
Mech Rating:	IP20/Nema1
Config Method:	Windows Hyper Terminal
UL certification:	E203225, Listed 67AM, UL-1604 Class 1, Div 2, GP A, B, C, D, Temp Code T4
ATEX certification:	ATEX 135419, II 3 G, EEx nL IIC T4, DEMKO 03
Power supply connector:	2-pole 5.08 mm Phoenix pluggable screw connector
AS-I baudrate:	167 kbit/s
AS-I connector:	2 x 2-pole 5.08 mm Phoenix pluggable screw connectors
FIPIO baudrate:	1 Mbit/s
FIPIO address:	Node address 0-99
FIPIO connector:	D-sub 9-pin male
Price Group:	C
Order Code:	AB7824