

## CANopen Slave - CANopen Slave



The Anybus X-gateway copies I/O-data in both directions thus enabling data exchange between the two networks. Default I/O configuration is 20 bytes Input and 20 bytes Output. Changing default settings is very simple and is carried out using the RS232 configuration port and a standard terminal interface on a PC, such as Hyper Terminal for Windows.

The gateway consists of two independent CANopen interfaces, logically and galvanically separated from each other.

Each of the two CANopen interfaces are adapter class products allowing fast data exchange. The CANopen slave's data map consists of Process Data Objects (fast data) and Service Data Objects (slow data). The data on the CANopen bus is updated when a change is made or on request from another node. The CANopen interface module is certified by the Can In Automation organisation and has proven conformance and interoperability with leading PLC's, SoftPLC's, HMI's etc

### KEY FEATURES

- CANopen PDO and SDO data objects supported
- CANopen Unscheduled data exchange support
- CANopen profile DS-301 v.4.02
- Customizable PDO-mapping
- Heartbeat and node guarding support
- Network Stor/Restore functionality

### TECHNICAL SPECIFICATIONS

|                                |   |
|--------------------------------|---|
| <b>Size:</b>                   | 126 mm x 110 mm x 42 mm   |
| <b>Power Supply:</b>           | 24 VDC (±10%)   |
| <b>Temperature:</b>            | 0-65°C  |
| <b>Current Consump:</b>        | max 300 mA  |
| <b>Baud Rate:</b>              | 10 kbit/s to 1 Mbit/s   |
| <b>I/O Input:</b>              | Default 20 bytes, max 512 bytes   |
| <b>I/O Output:</b>             | Default 20 bytes, max 512 bytes   |
| <b>Mech Rating:</b>            | IP20/Nema1  |
| <b>Config Method:</b>          | Windows Hyper Terminal  |
| <b>UL certification:</b>       | E203225, Listed 67AM, UL-1604 Class 1, Div 2, GP A, B, C, D, Temp Code T4 |
| <b>ATEX certification:</b>     | ATEX 135419, II 3 G, EEx nL IIC T4, DEMKO 03                              |
| <b>Power supply connector:</b> | 2-pole 5.08 mm Phoenix pluggable screw connector                          |
| <b>CANopen connectors:</b>     | D-sub 9-pin male  |
| <b>CANopen address:</b>        | Node address 1-99   |
| <b>CANopen config.:</b>        | Configured by CanOpen Master via EDS file (provided by HMS)               |
| <b>Price Group:</b>            | B   |
| <b>Order Code:</b>             | AB7894  |