

Modbus RTU Slave - CC Link Slave



The Anybus X-gateway copies I/O-data in both directions thus enabling data exchange between the two networks. Default I/O configuration is 20 bytes Input and 20 bytes Output. Changing default settings is very simple and is carried out using the RS232 configuration port and a standard terminal interface on a PC, such as Hyper Terminal for Windows.

The Modbus RTU Slave interface is implemented according to Modbus Protocol ref guide (PI-MBUS-300). All data is mapped to 3x and 4x Modbus areas meaning the Input Status and Output Register Word areas. The Modbus RTU standard baudrate is 19200 Bit/s but can be modified on the gateway between 1200 Bit/s to 57 600 Bit/s.

The CC-Link interface is a slave module for the CC-Link fieldbus system. It contains all the functionality needed to turn an application into a complete CC-Link remote device and it is configured to use the generic PLC profile. The CC-Link interface module is certified by the CLPA organisation and has proven conformance and interoperability with leading PLC's, HMI's etc

KEY FEATURES

- Supported Modbus RTU functions: 1, 2, 3, 4, 5, 6, 8, 15, 16, 22, 23
- Uses up to 4 occupied stations on CC-Link - configurable size
- Uses the CC-Link PLC profile for data exchange
- Modbus RTU transmission media RS485

TECHNICAL SPECIFICATIONS

Size:	126 mm x 110 mm x 42 mm
Power Supply:	24 VDC (±10%)
Temperature:	0-65°C
Current Consump:	max 300 mA
I/O Input:	Default 20 bytes, max 64 bytes (max 128 I/O-points and 16 words on CC-Link)
I/O Output:	Default 20 bytes, max 64 bytes (max 128 I/O-points and 16 words on CC-Link)
Mech Rating:	IP20/Nema1
Config Method:	Windows Hyper Terminal
UL certification:	E203225, Listed 67AM, UL-1604 Class 1, Div 2, GP A, B, C, D, Temp Code T4
ATEX certification:	ATEX 135419, II 3 G, EEx nL IIC T4, DEMKO 03
Power supply connector:	2-pole 5.08 mm Phoenix pluggable screw connector
Modbus RTU baudrate:	1200 Bit/s to 57 600 Bit/s
Modbus RTU address:	Node address 1-247
Modbus RTU connector:	D-sub 9-pin female
CC-Link baudrate:	156kbps to 10Mbps
CC-Link address:	Station 1-64
CC-Link connector:	5-pole 5.08 mm Phoenix pluggable screw connector
CC-Link config.:	Configured by CC Link Master via CSP Config file (provided by HMS)
Price Group:	B
Order Code:	AB7621