



The Anybus X-gateway copies I/O-data in both directions thus enabling data exchange between the two networks. Default I/O configuration is 20 bytes Input and 20 bytes Output. Changing default settings is very simple and is carried out using the RS232 configuration port and a standard terminal interface on a PC, such as Hyper Terminal for Windows.

The Ethernet interface consists of an embedded Ethernet/IP 10/100 Mbit/s interface with IT functionality such as WEB-server, SSI-scripts, Flash file system, FTP-server, Email client, Telnet etc. It is possible to build web pages displaying and controlling a factory floor process with data from the other connected network. It is built on a dedicated 32 bit RISC micro processor (+60 mips) ensuring fast and secure Ethernet performance. The EtherNet/IP interface module is certified by the ODVA and has proven conformance and interoperability with leading PLC's, HMI's etc

The ControlNet interface is implemented according to the ControlNet international specification for a Communication adapter (profile number 12). A connection to the Anybus-S ControlNet module can be opened from a ControlNet scanner. The size of the connection can be up to 450 bytes in each direction. The ControlNet module can be read or written to by UCMM (Unscheduled) messages from another ControlNet adapter (slave) or scanner (master). The module is equipped with two BNC contacts for connection to ControlNet. If redundant operation is desired, both connectors are used; otherwise either connector A or B is used. The module is also equipped with a NAP (Network access port) for temporary connection of configuration tools. The minimum Network update time, (NUT), of the module is 5ms. The ControlNet interface module is certified by the ODVA and has proven conformance and interoperability with leading PLC's, HMI's etc

KEY FEATURES

- Ethernet 10/100 Mbit/s twisted pair RJ45 connection
- TCP/IP settings configurable with web-page, Configuration Tool, DHCP, ARP or with DIP switches
- Ethernet/IP level 2 I/O Server CIP
- 1.4 Mbyte storage space on Flash disc
- Support for AnyBus IPconfig utility for easy TCP/IP set up
- SSI scripts used for easy display/control of process data on webpages
- Gateway diagnostics via WEB-pages
- Multicasts of both inputs and peer-to peer data on ControlNet
- ControlNet Media redundancy
- ControlNet Specification version: Communications Adapter profile 12

TECHNICAL SPECIFICATIONS

Size:	126 mm x 110 mm x 42 mm
Power Supply:	24 VDC (±10%)
Temperature:	0-65°C
Current Consump:	max 300 mA
I/O Input:	Default 20 bytes, max 512 bytes (max 450 bytes as I/O on ControlNet)
I/O Output:	Default 20 bytes, max 512 bytes (max 450 bytes as I/O on ControlNet)
Mech Rating:	IP20/Nema1
Config Method:	Windows Hyper Terminal
UL certification:	E203225, Listed 67AM, UL-1604 Class 1, Div 2, GP A, B, C, D, Temp Code T4
ATEX certification:	ATEX 135419, II 3 G, EEx nL IIC T4, DEMKO 03
Power supply connector:	2-pole 5.08 mm Phoenix pluggable screw connector
Ethernet/IP baudrate:	10/100 Mbit/s autodetect
Ethernet connector:	RJ45
Ethernet/IP address:	Any valid IP-address
Ethernet/IP config.:	Configured by EtherNet/IP Scanner via EDS file (provided by HMS)
ControlNet baudrate:	5Mbit/s
ControlNet MacID:	1-99
ControlNet connector:	Dual BNC coaxial connectors
ControlNet config.:	Configured by ControlNet Scanner via EDS file (provided by HMS)
Price Group:	C
Order Code:	AB7834