



ControlNet Adapter/Slave - Modbus Plus Slave



The Anybus X-gateway copies I/O-data in both directions thus enabling data exchange between the two networks. Default I/O configuration is 20 bytes Input and 20 bytes Output. Changing default settings is very simple and is carried out using the RS232 configuration port and a standard terminal interface on a PC, such as Hyper Terminal for Windows.

The ControlNet interface is implemented according to the ControlNet international specification for a Communication adapter (profile number 12). A connection to the Anybus-S ControlNet module can be opened from a ControlNet scanner. The size of the connection can be up to 450 bytes in each direction. The ControlNet module can be read or written to by UCMM (Unscheduled) messages from another ControlNet adapter (slave) or scanner (master). The module is equipped with two BNC contacts for connection to ControlNet. If redundant operation is desired, both connectors are used; otherwise either connector A or B is used. The module is also equipped with a NAP (Network access port) for temporary connection of configuration tools. The minimum Network update time, (NUT), of the module is 5ms. The ControlNet interface module is certified by the ODVA and has proven conformance and interoperability with leading PLC's, HMI's etc

The Modbus Plus interface is based on licensed chip-set and software from Modicon Inc. Supporting both the Global Database and Register mapping to 3x and 4x registers this module implements a versatile Modbus Plus interface. The Modbus Plus interface module is certified by the Modconnect and has proven conformance and interoperability with leading PLC's, HMI's etc

KEY FEATURES

- Multicasts of both inputs and peer-to peer data on ControlNet
- ControlNet Media redundancy
- ControlNet Specification version: Communications Adapter profile 12
- Modbus Plus Global Data Base Transaction, Point-to-Point commands, Read holding registers, Preset single register
- Modbus Plus Host Firmware Rev. 77

TECHNICAL SPECIFICATIONS

Size:	126 mm x 110 mm x 42 mm
Power Supply:	24 VDC (±10%)
Temperature:	0-65°C
Current Consump:	max 300 mA
I/O Input:	Default 20 bytes, max 512 bytes (max 64 bytes as Modbus Plus Global Data, max 450 bytes as I/O on ControlNet)
I/O Output:	Default 20 bytes, max 512 bytes (max 64 bytes as Modbus Plus Global Data, max 450 bytes as I/O on ControlNet)
Mech Rating:	IP20/Nema1
Config Method:	Windows Hyper Terminal
UL certification:	E203225, Listed 67AM, UL-1604 Class 1, Div 2, GP A, B, C, D, Temp Code T4
ATEX certification:	ATEX 135419, II 3 G, EEx nL IIC T4, DEMKO 03
Power supply connector:	2-pole 5.08 mm Phoenix pluggable screw connector
ControlNet baudrate:	5Mbit/s
ControlNet MacID:	1-99
ControlNet connector:	Dual BNC coaxial connectors
ControlNet config.:	Configured by ControlNet Scanner via EDS file (provided by HMS)
Modbus Plus baudrate:	1 Mbit/s
Modbus Plus address:	Node-ID and Source-ID 1-64
ModbusPlus connector:	D-sub 9-pin female
Price Group:	C
Order Code:	AB7870