

## DeviceNet Scanner/Master - Profinet IO Device



The Anybus X-gateway copies I/O-data in both directions thus enabling data exchange between the two networks. Default I/O configuration is 20 bytes Input and 20 bytes Output. Changing default settings is very simple and is carried out using the RS232 configuration port and a standard terminal interface on a PC, such as Hyper Terminal for Windows.

The DeviceNet Master interface can act both as a Master/Scanner and/or Adapter/Slave. The entire DeviceNet protocol is implemented into the module. The module manages control of up to 63 DeviceNet slaves. Full DeviceNet configuration can be defined and loaded into the Anybus-M module via the HMS configuration software NetTool-DN (purchased as a separate accessory) or via Rockwell's RSNetWorx.

The Profinet IO interface is a complete solution for a Profinet IO slave Device. The module is based on the Siemens Profinet IO software technology.

The Profinet IO baudrate is 100Mbit/s (full duplex). The IP-address and additional IP-settings is easily configured with the Anybus IPconfig utility for Windows. Additional ways to set the IP-address are either via DHCP or Profinet configuration tool. Four diagnostic LEDs will continuously indicate the actual Profinet IO status and possible error messages. The Profinet IO interface uses a normal RJ45 connector for the bus connection.

IT-functions like WEB-server, E-mail client, FTP-server are also supported. The IT functions can be used simultaneously with the Profinet IO communication.

Modbus/TCP is also supported with "Read Data" functions.

### KEY FEATURES

- Complete DeviceNet 2.0 scanner implementation according to ODVA
- DeviceNet Group 2 Client/Server / UCMM support
- Manages up to 63 DeviceNet slaves
- DeviceNet Configuration via AnyBus NetTool-DN or RSNetworx
- DeviceNet Explicit peer to peer messaging, configuration consistency value. I/O Slave messaging: Bit strobe, Polling, Cyclic & Change of State (COS)
- Dynamical web-server with flash disc
- E-Mail Client, FTP & Telnet Server
- Ethernet baudrate 100 Mbit/S
- Profinet IO and IT functions
- 1 Mbyte storage space on Flash disc
- TCP/IP settings configurable with Profinet config tool, Anybus IPconfig or DHCP

### TECHNICAL SPECIFICATIONS

<b>Size:</b>	126 mm x 110 mm x 42 mm
<b>Power Supply:</b>	24 VDC (±10%)
<b>Temperature:</b>	0-65°C°C
<b>Current Consump:</b>	max 300 mA
<b>I/O Input:</b>	Default 20 bytes, max 512 bytes
<b>I/O Output:</b>	Default 20 bytes, max 512 bytes
<b>Mech Rating:</b>	IP20/Nema1
<b>Config Method:</b>	Windows Hyper Terminal and NetTool for Devicenet or RS-Network
<b>UL certification:</b>	E203225, Listed 67AM, UL-1604 Class 1, Div 2, GP A, B, C, D, Temp Code T4
<b>ATEX certification:</b>	ATEX 135419, II 3 G, EEx nL IIC T4, DEMKO 03
<b>Power supply connect:</b>	2-pole 5.08 mm Phoenix pluggable screw connector
<b>DeviceNet baudrate:</b>	125-500 kbit/s
<b>DeviceNet MacID:</b>	0-63
<b>DeviceNet connector:</b>	5-pole 5.08 mm Phoenix pluggable screw connector
<b>Accessory order code:</b>	018020 (NetTool-DN configuration Tool for DeviceNet)
<b>Profinet connector:</b>	RJ45
<b>Profinet baudrate:</b>	100Mbit/s
<b>Price Group:</b>	C
<b>Order Code:</b>	AB7647