

DeviceNet Adapter/Slave - Interbus Slave Cu



The Anybus X-gateway copies I/O-data in both directions thus enabling data exchange between the two networks. Default I/O configuration is 20 bytes Input and 20 bytes Output. Changing default settings is very simple and is carried out using the RS232 configuration port and a standard terminal interface on a PC, such as Hyper Terminal for Windows.

The high performance DeviceNet Slave interface provides instant connectivity to the DeviceNet network. The module conforms to DeviceNet 2.0. The DeviceNet interface module is certified by the ODVA and has proven conformance and interoperability with leading PLC's, HMI's etc. Baud rate and MAC ID can be set via DIP switches.

The Interbus 2Mbit/s interface module is a slave node that can be read from/written to by an Interbus master. Interbus has two ways of exchanging data; one through fast cyclical I/O data called ?Process Data?, and one through a somewhat slower protocol called PCP, which is mainly used for configuration purposes. It supports Interbus PCP V2.0. The module supports up to 10 words of data on the bus, out of which up to four words can be used for PCP.

KEY FEATURES

- DeviceNet Specification version: Vol 1: 2.0, Vol 2: 2.0
- Conformance test version: A-12
- I/O Slave messaging: Bit strobe, Polling, Cyclic, COS and Explicit Messaging
- Individually isolated Bus In and Bus Out Interbus interfaces
- Up to 10 words of Process data on Interbus
- Interbus PCP v2.0 (0, 1, 2 or 4 words)

TECHNICAL SPECIFICATIONS

Size:	126 mm x 110 mm x 42 mm
Power Supply:	24 VDC (±10%)
Temperature:	0-65°C
Current Consump:	max 300 mA
I/O Input:	20 bytes, max 512 bytes (max 20 bytes as I/O on Interbus)
I/O Output:	20 bytes, max 512 bytes (max 20 bytes as I/O on Interbus)
Mech Rating:	IP20/Nema1
Config Method:	Windows Hyper Terminal
UL certification:	E203225, Listed 67AM, UL-1604 Class 1, Div 2, GP A, B, C, D, Temp Code T4
ATEX certification:	ATEX 135419, II 3 G, EEx nL IIC T4, DEMKO 03
Power supply connector:	2-pole 5.08 mm Phoenix pluggable screw connector
DeviceNet baud rate:	125-500 kbit/s
DeviceNet MacID:	0-63
DeviceNet connector:	5-pole 5.08 mm Phoenix pluggable screw connector
DeviceNet config.:	Configured by DeviceNet Scanner via EDS file (provided by HMS)
Interbus Baudrate:	500Kbit/s or 2Mbit/s
Interbus connectors:	D-sub 9-pin ? Bus In male, Bus Out female
Price Group:	C
Order Code:	AB7857