



## Ethernet ModbusTCP Slave - DeviceNet Adapter/Slave



The Anybus X-gateway copies I/O-data in both directions thus enabling data exchange between the two networks. Default I/O configuration is 20 bytes Input and 20 bytes Output. Changing default settings is very simple and is carried out using the RS232 configuration port and a standard terminal interface on a PC, such as Hyper Terminal for Windows.

The Ethernet interface consists of an embedded ModbusTCP 10/100 Mbit/s interface with IT functionality such as WEB-server, SSI-scripts, Flash file system, FTP-server, Email client, Telnet etc. It is possible to build web pages displaying and controlling a factory floor process with data from the other connected network. It is built on a dedicated 32 bit RISC micro processor (+60 mips) ensuring fast and secure Ethernet performance. The EtherNet/ModbusTCP interface module is certified by the Univeristy of Michigan and has proven conformance and interoperability with leading PLC's, HMI's etc.

The high performance DeviceNet Slave interface provides instant connectivity to the DeviceNet network. The module conforms to DeviceNet 2.0. The DeviceNet interface module is certified by the ODVA and has proven conformance and interoperability with leading PLC's, HMI's etc. Baud rate and MAC ID can be set via DIP switches.

### KEY FEATURES

- 10/100 MBit twisted pair RJ45 connection
- TCP/IP settings configurable with web-page, Configuration Tool, DHCP, ARP or with DIP switches
- Modbus/TCP class 0, class 1 and partially class 2 slave functionality
- 1.4 Mbyte storage space on Flash disk
- Support for AnyBus IPconfig utility for easy TCP/IP set up
- SSI scripts used for easy display/control of process data on WEB-pages
- Gateway diagnostics via WEB-pages
- DeviceNet Specification version: Vol 1: 2.0, Vol 2: 2.0
- Conformance test version: A-12
- I/O Slave messaging: Bit strobe, Polling, Cyclic, COS and Explicit Messaging

### TECHNICAL SPECIFICATIONS

<b>Size:</b>	126 mm x 110 mm x 42 mm
<b>Power Supply:</b>	24 VDC (±10%)
<b>Temperature:</b>	0-65°C
<b>Current Consump:</b>	max 300 mA
<b>I/O Input:</b>	Default 20 bytes, max 512 bytes
<b>I/O Output:</b>	Default 20 bytes, max 512 bytes
<b>Mech Rating:</b>	IP20/Nema1
<b>Config Method:</b>	Windows Hyper Terminal
<b>UL certification:</b>	E203225, Listed 67AM, UL-1604 Class 1, Div 2, GP A, B, C, D, Temp Code T4
<b>ATEX certification:</b>	ATEX 135419, II 3 G, EEx nL IIC T4, DEMKO 03
<b>Power supply connector:</b>	2-pole 5.08 mm Phoenix pluggable screw connector
<b>Modbus-TCP baudrate:</b>	10/100 Mbit/s autodetect
<b>Modbus-TCP connector:</b>	RJ45
<b>Modbus-TCP address:</b>	Any valid IP-address
<b>DeviceNet baud rate:</b>	125-500 kbit/s
<b>DeviceNet MacID:</b>	0-63
<b>DeviceNet connector:</b>	5-pole 5.08 mm Phoenix pluggable screw connector
<b>DeviceNet config.:</b>	Configured by DeviceNet Scanner via EDS file (provided by HMS)
<b>Price Group:</b>	B
<b>Order Code:</b>	AB7635