

Ethernet/IP Adapter/Slave - FIP Slave



The Anybus X-gateway copies I/O-data in both directions thus enabling data exchange between the two networks. Default I/O configuration is 20 bytes Input and 20 bytes Output. Changing default settings is very simple and is carried out using the RS232 configuration port and a standard terminal interface on a PC, such as Hyper Terminal for Windows.

The Ethernet interface consists of an embedded Ethernet/IP 10/100 Mbit/s interface with IT functionality such as WEB-server, SSI-scripts, Flash file system, FTP-server, Email client, Telnet etc. It is possible to build web pages displaying and controlling a factory floor process with data from the other connected network. It is built on a dedicated 32 bit RISC micro processor (+60 mips) ensuring fast and secure Ethernet performance. The EtherNet/IP interface module is certified by the ODVA and has proven conformance and interoperability with leading PLC's, HMI's etc

The FIPIO interface is based an embedded Anybus-S module providing industrial performance and quality. FIPIO station address can be selected via switches on the end side of the module. A transformer connection on the module provides a isolated fieldbus interface.

KEY FEATURES

- Ethernet 10/100 Mbit/s twisted pair RJ45 connection
- TCP/IP settings configurable with web-page, Configuration Tool, DHCP, ARP or with DIP switches
- Ethernet/IP level 2 I/O Server CIP
- 1.4 Mbyte storage space on Flash disk
- Support for AnyBus IPconfig utility for easy TCP/IP set up
- SSI scripts used for easy display/control of process data on webpages
- Gateway diagnostics via WEB-pages
- Supports both FIP and WorldFIP standards
- FIPIO profile FEDP (Extended Device Profile), class 0
- Transformer isolated FIP interface

TECHNICAL SPECIFICATIONS

Size:	126 mm x 110 mm x 42 mm
Power Supply:	24 VDC (±10%)
Temperature:	0-65°C
Current Consump:	max 300 mA
I/O Input:	Default 20 bytes, max 64 bytes
I/O Output:	Default 20 bytes, max 64 bytes
Mech Rating:	IP20/Nema1
Config Method:	Windows Hyper Terminal
UL certification:	E203225, Listed 67AM, UL-1604 Class 1, Div 2, GP A, B, C, D, Temp Code T4
ATEX certification:	ATEX 135419, II 3 G, EEx nL IIC T4, DEMKO 03
Power supply connector:	2-pole 5.08 mm Phoenix pluggable screw connector
Ethernet/IP baudrate:	10/100 Mbit/s autodetect
Ethernet connector:	RJ45
Ethernet/IP address:	Any valid IP-address
Ethernet/IP config.:	Configured by EtherNet/IP Scanner via EDS file (provided by HMS)
FIPIO baudrate:	1 Mbit/s
FIPIO address:	Node address 0-99
FIPIO connector:	D-sub 9-pin male
Price Group:	C
Order Code:	AB7835