

## FIP Slave - Interbus Slave Cu



The Anybus X-gateway copies I/O-data in both directions thus enabling data exchange between the two networks. Default I/O configuration is 20 bytes Input and 20 bytes Output. Changing default settings is very simple and is carried out using the RS232 configuration port and a standard terminal interface on a PC, such as Hyper Terminal for Windows.

The FIPIO interface is based on an embedded Anybus-S module providing industrial performance and quality. FIPIO station address can be selected via switches on the end side of the module. A transformer connection on the module provides a isolated fieldbus interface.

The Interbus 2Mbit/s interface module is a slave node that can be read from/written to by an Interbus master. Interbus has two ways of exchanging data; one through fast cyclical I/O data called 'Process Data', and one through a somewhat slower protocol called PCP, which is mainly used for configuration purposes. It supports Interbus PCP V2.0. The module supports up to 10 words of data on the bus, out of which up to four words can be used for PCP.

### KEY FEATURES

- Supports both FIP and WorldFIP standards
- FIPIO profile FEDP (Extended Device Profile), class 0
- Transformer isolated FIP interface
- Individually isolated Bus In and Bus Out Interbus interfaces
- Up to 10 words of Process data on Interbus
- Interbus PCP v2.0 (0, 1, 2 or 4 words)

### TECHNICAL SPECIFICATIONS

<b>Size:</b>	126 mm x 110 mm x 42 mm
<b>Power Supply:</b>	24 VDC (±10%)
<b>Temperature:</b>	0-65°C
<b>Current Consump:</b>	max 300 mA
<b>I/O Input:</b>	Default 20 bytes, max 64 bytes (max 20 bytes as I/O on Interbus)
<b>I/O Output:</b>	Default 20 bytes, max 64 bytes (max 20 bytes as I/O on Interbus)
<b>Mech Rating:</b>	IP20/Nema1
<b>Config Method:</b>	Windows Hyper Terminal
<b>UL certification:</b>	E203225, Listed 67AM, UL-1604 Class 1, Div 2, GP A, B, C, D, Temp Code T4
<b>ATEX certification:</b>	ATEX 135419, II 3 G, EEx nL IIC T4, DEMKO 03
<b>Power supply connector:</b>	2-pole 5.08 mm Phoenix pluggable screw connector
<b>FIPIO baudrate:</b>	1 Mbit/s
<b>FIPIO address:</b>	Node address 0-99
<b>FIPIO connector:</b>	D-sub 9-pin male
<b>Interbus Baudrate:</b>	500Kbit/s or 2Mbit/s
<b>Interbus connectors:</b>	D-sub 9-pin ? Bus In male, Bus Out female
<b>Price Group:</b>	C
<b>Order Code:</b>	AB7874