



The Anybus X-gateway copies I/O-data in both directions thus enabling data exchange between the two networks. Default I/O configuration is 20 bytes Input and 20 bytes Output. Changing default settings is very simple and is carried out using the RS232 configuration port and a standard terminal interface on a PC, such as Hyper Terminal for Windows.

The FIPIO interface is based on an embedded Anybus-S module providing industrial performance and quality. FIPIO station address can be selected via switches on the end side of the module. A transformer connection on the module provides a isolated fieldbus interface.

The LonWorks interface is a high performance interface to LonWorks networks. The interface supports LonMark objects handling. The required network variables on the LonWorks side can be configured and stored in FLASH. It is based on MIP that allows high throughput and a configurable set of up to 256 input and 256 output network variables. The interface can, via the "LWtool" PC-based configuration utility program, link, and convert data between the other network side and devices located on a LonWorks Network. The LonWorks side of the product can be configured for any type of network variable e.g. SNVT's or UNVT's.

KEY FEATURES
■ Supports both FIP and WorldFIP standards
■ FIPIO profile FEDP (Extended Device Profile), class 0
■ Transformer isolated FIP interface
■ Special LW Config Software Tool for Network variable Setup
■ Certification prepared for Lonmark application layer interoperability guidelines V3.2
■ LonWorks FT-X1 Transceiver

TECHNICAL SPECIFICATIONS
Size: 126 mm x 110 mm x 42 mm
Power Supply: 24 VDC (±10%)
Temperature: 0-65°C
Current Consump: max 300 mA
I/O Input: Default 20 bytes, max 64 bytes (32 network variables on LonWorks)
I/O Output: Default 20 bytes, max 64 bytes (32 network variables on LonWorks)
Mech Rating: IP20/Nema1
Config Method: Windows Hyper Terminal
UL certification: E203225, Listed 67AM, UL-1604 Class 1, Div 2, GP A, B, C, D, Temp Code T4
ATEX certification: ATEX 135419, II 3 G, EEx nL IIC T4, DEMKO 03
Power supply connector: 2-pole 5.08 mm Phoenix pluggable screw connector
FIPIO baudrate: 1 Mbit/s
FIPIO address: Node address 0-99
FIPIO connector: D-sub 9-pin male
LonWorks baudrate: 78 kbit/s
LonWorks Connector: 5-pole 5.08 mm Phoenix pluggable screw connector
Price Group: C
LonWorks config.: Order code: 018640 - (LW Tool ABX for LonWorks interface variable configuration)
Order Code: AB7880