

Profibus Slave - FIP Slave



The Anybus X-gateway copies I/O-data in both directions thus enabling data exchange between the two networks. Default I/O configuration is 20 bytes Input and 20 bytes Output. Changing default settings is very simple and is carried out using the RS232 configuration port and a standard terminal interface on a PC, such as Hyper Terminal for Windows.

The Profibus DP/DPV1 slave interface is implemented according to the standard IEC61158 as a modular slave, supporting all standard functionality such as Watchdog, Sync and Freeze and diagnostics. Standard DP as well as DPV1 acyclic data services (Class1/Class2) are supported. The Profibus interface module is certified by the Profibus user organization and has proven conformance and interoperability with leading PLC's, HMI's etc. Profibus address is set via rotary switches 0-99.

The FIPIO interface is based on an embedded Anybus-S module providing industrial performance and quality. FIPIO station address can be selected via switches on the end side of the module. A transformer connection on the module provides a isolated fieldbus interface.

KEY FEATURES

- Watchdog support
- Sync and Freeze
- Supports PA baud rate 45.45 kbit/s
- Supports both FIP and WorldFIP standards
- FIPIO profile FEDP (Extended Device Profile), class 0
- Transformer isolated FIP interface
- Complete Profibus DP and DPV1 (Class1/Class2) slave functionality according to IEC 61158

TECHNICAL SPECIFICATIONS

Size:	126 mm x 110 mm x 42 mm
Power Supply:	24 VDC (±10%)
Temperature:	0-65°C
Current Consump:	max 300 mA
I/O Input:	Default 20 bytes, max 64 bytes
I/O Output:	Default 20 bytes, max 64 bytes
Mech Rating:	IP20/Nema1
Config Method:	Windows Hyper Terminal
UL certification:	E203225, Listed 67AM, UL-1604 Class 1, Div 2, GP A, B, C, D, Temp Code T4
ATEX certification:	ATEX 135419, II 3 G, EEx nL IIC T4, DEMKO 03
Power supply connector:	2-pole 5.08 mm Phoenix pluggable screw connector
Profibus baudrate:	9600 bit/s - 12 Mbit/s autodetect
Profibus address:	Node address 0-99
Profibus connector:	D-sub 9-pin female
Profibus config.:	Configured by Profibus Master via GSD file (provided by HMS)
FIPIO baudrate:	1 Mbit/s
FIPIO address:	Node address 0-99
FIPIO connector:	D-sub 9-pin male
Price Group:	C
Order Code:	AB7846