

Ethernet ModbusTCP Slave - Interbus Slave Cu



The Anybus X-gateway copies I/O-data in both directions thus enabling data exchange between the two networks. Default I/O configuration is 20 bytes Input and 20 bytes Output. Changing default settings is very simple and is carried out using the RS232 configuration port and a standard terminal interface on a PC, such as Hyper Terminal for Windows.

The Ethernet interface consists of an embedded ModbusTCP 10/100 Mbit/s interface with IT functionality such as WEB-server, SSI-scripts, Flash file system, FTP-server, Email client, Telnet etc. It is possible to build web pages displaying and controlling a factory floor process with data from the other connected network. It is built on a dedicated 32 bit RISC micro processor (+60 mips) ensuring fast and secure Ethernet performance.

The EtherNet/ModbusTCP interface module is certified by the Univeristy of Michigan and has proven conformance and interoperability with leading PLC's, HMI's etc.

The Interbus 2Mbit/s interface module is a slave node that can be read from/written to by an Interbus master. Interbus has two ways of exchanging data; one through fast cyclical I/O data called 'Process Data', and one through a somewhat slower protocol called PCP, which is mainly used for configuration purposes. It supports Interbus PCP V2.0. The module supports up to 10 words of data on the bus, out of which up to four words can be used for PCP.

KEY FEATURES

- 10/100 MBit twisted pair RJ45 connection
- TCP/IP settings configurable with web-page, Configuration Tool, DHCP, ARP or with DIP switches
- Modbus/TCP class 0, class 1 and partially class 2 slave functionality
- 1.4 Mbyte storage space on Flash disk
- Support for AnyBus IPconfig utility for easy TCP/IP set up
- SSI scripts used for easy display/control of process data on WEB-pages
- Gateway diagnostics via WEB-pages
- Individually isolated Bus In and Bus Out Interbus interfaces
- Up to 10 words of Process data on Interbus
- Interbus PCP v2.0 (0, 1, 2 or 4 words)

TECHNICAL SPECIFICATIONS

Size:	126 mm x 110 mm x 42 mm
Power Supply:	24 VDC (±10%)
Temperature:	0-65°C
Current Consump:	max 300 mA
I/O Input:	Default 20 bytes, max 512 bytes (max 20 bytes as I/O on Interbus)
I/O Output:	Default 20 bytes, max 512 bytes (max 20 bytes as I/O on Interbus)
Mech Rating:	IP20/Nema1
Config Method:	Windows Hyper Terminal
UL certification:	E203225, Listed 67AM, UL-1604 Class 1, Div 2, GP A, B, C, D, Temp Code T4
ATEX certification:	ATEX 135419, II 3 G, EEx nL IIC T4, DEMKO 03
Power supply connector:	2-pole 5.08 mm Phoenix pluggable screw connector
Modbus-TCP baudrate:	10/100 Mbit/s autodetect
Modbus-TCP connector:	RJ45
Modbus-TCP address:	Any valid IP-address
Interbus Baudrate:	500Kbit/s or 2Mbit/s
Interbus connectors:	D-sub 9-pin ? Bus In male, Bus Out female
Price Group:	B
Order Code:	AB7638