

echolink and echochange

Accessories



Connector power pack 24 V DC

Connector power pack 24 V DC

- 100 - 240 V AC, 47 - 63 Hz, sec. 24 V, 1,25A

	Order numbers:
Version EURO	700-5596-01
Version UK	700-5596-02
Version USA	700-5596-03



RS232 – TTY (20 mA)
9pin female – 15pin male

Connection cable RS232 – PLC TTY

- Connection cable RS232 – TTY
- RS232, 9pin D-sub female – TTY (20 mA), 15pin D-sub male

	Order numbers:
5 meters	700-1500-05
10 meters	700-1500-10
15 meters	700-1500-15

APPLICATION:

- echolink with RS232
 - PC and other devices with RS232
- } S5 PG interface



echolink TTY – AG TTY
9pin female – 15pin male

Connection cable echolink TTY – PLC TTY

- echolink TTY, 9pin D-sub female – TTY, 15pin D-sub male

	Order numbers:
Basic cable 1 meter	700-1800-01
Each additional meter	700-1800-xx (xx = Length in meters)

APPLICATION:

- echolink with TTY (20 mA) to S5 PG





echolink TTY – PLC (AS511)
9pin female – 25pin female

Connection cable echolink TTY – PLC TTY (25pin)

- echolink TTY, 9pin D-sub female – PLC (AS511), 25pin D-sub female

		Order numbers:
	Basic cable 1 meter	700-1850-01
	Each additional meter	700-1850-xx (xx = Length in meters)

APPLICATION:

- echolink with TTY (20 mA) to S5 PG (e.g. AG 150)



RS232 – PPI cable
9pin female – 9pin male

RS232 – PPI cable

- PPI cable for the connection with a S7-200
- RS232, 9pin D-sub female – PPI, 9pin D-sub male
- Length: 3 meters

	Order number:	700-6100-01
--	---------------	-------------

APPLICATION:

- echolink with RS232 to S7-200 PG interface



USB – RS232 converter cable

USB – RS232 converter cable

- Converter cable USB – RS232
- USB-A connector – RS232, 9pin D-sub male
- Length: 0,35 meters

	Order number:	900-8300-01
--	---------------	-------------