

Two devices on one PG interface at the same time.
Compatible with all S5 PLCs.

AREAS OF APPLICATION

- Simultaneous operation of programming device, text display, operator panel or other process devices

PG-MUX II




PG-MUX II

- For two PGs, including connection cable (see below)

PLC interface:	TTY (20 mA), active
PG1 + PG2 interface:	TTY (20 mA), active
Protocols:	2 x AS511 or 1 x Sinec-L1-BUS and 1 x AS511
Power supply:	230 V AC and 24 V DC
Dimensions [in mm]:	L = 190, D = 110, H = 50
Order number:	400-9361-05

MINI-MUX



MINI-MUX

- For one PG and one OP, exclusive of connection cable

PLC interface:	TTY (20 mA), active
PG interface:	TTY (20 mA), active
Protocol:	AS511
OP interface:	TTY passive
Protocols:	AS511 or Sinec-L1-BUS
Power supply:	24 V DC
Dimensions [in mm]:	L = 135, D = 110, H = 50
Order number:	400-9361-01

Accessories: Connection cable Multiplexer – PLC TTY



Connection cable
Multiplexer – PLC TTY

- TTY, 15pin D-sub male – TTY, 15pin D-sub female
- Included in the scope of supply of PG-MUX
- Length: 3 meters

Order number:	400-9361-03
---------------	-------------